

# CSS MARKER PAINT

Chemwatch Material Safety Data Sheet

Issue Date: 27-May-2008

NC317ECP

CHEMWATCH 15-6780

Version No:2.0

CD 2008/2 Page 1 of 14

---

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

---

### PRODUCT NAME

CSS MARKER PAINT

### PROPER SHIPPING NAME

AEROSOLS

### PRODUCT USE

Application is by spray atomisation from a hand held aerosol pack. Fast drying marker paint.

### SUPPLIER

Company: Construction Supply Specialists Pty Ltd

Address:

PO Box 155

Campbellfield

VIC, 3061

AUS

Company: Construction Supply Specialists Pty Ltd

Address:

6 Broadfield Road

Broadmeadows

VIC, 3047

AUS

Telephone: +61 3 9357 4228

Emergency phone: 02 9673 4488 (Aerocan)

Fax: +61 3 9357 4229

---

## Section 2 - HAZARDS IDENTIFICATION

---

### STATEMENT OF HAZARDOUS NATURE

**HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.**

### POISONS SCHEDULE

S5

### RISK

Extremely flammable.

Harmful by inhalation and in contact with skin.

Irritating to eyes respiratory system and skin.

Risk of explosion if heated under confinement.

Vapours may cause drowsiness and dizziness.

### SAFETY

Wear suitable protective clothing.

To clean the floor and all objects contaminated by this material use water and detergent.

Keep away from food drink and animal feeding stuffs.

If swallowed IMMEDIATELY contact Doctor or Poisons Information Centre (show this container or label).

This material and its container must be disposed of as hazardous waste.

---

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

---

NAME	CAS RN	%
acetone	67-64-1	30-60
aromatic hydrocarbons	63231-51-6	10-30
alkyd resin		<10
driers		<10
hydrocarbon propellant	68476-85-7.	10-30

continued...

# CSS MARKER PAINT

Chemwatch Material Safety Data Sheet

Issue Date: 27-May-2008

NC317ECP

CHEMWATCH 15-6780

Version No:2.0

CD 2008/2 Page 2 of 14

---

## Section 4 - FIRST AID MEASURES

---

### SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

### EYE

If aerosols come in contact with the eyes:

- Immediately hold the eyelids apart and flush the eye with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

### NOTES TO PHYSICIAN

For acute or short term repeated exposures to acetone:

- Symptoms of acetone exposure approximate ethanol intoxication.
- About 20% is expired by the lungs and the rest is metabolised. Alveolar air half-life is about 4 hours following two hour inhalation at levels near the Exposure Standard; in overdose, saturable metabolism and limited clearance, prolong the elimination half-life to 25-30 hours.

- There are no known antidotes and treatment should involve the usual methods of decontamination followed by supportive care.

[Ellenhorn and Barceloux: Medical Toxicology]

Management:

Measurement of serum and urine acetone concentrations may be useful to monitor the severity of ingestion or inhalation.

Inhalation Management:

- Maintain a clear airway, give humidified oxygen and ventilate if necessary.
- If respiratory irritation occurs, assess respiratory function and, if necessary, perform chest X-rays to check for chemical pneumonitis.
- Consider the use of steroids to reduce the inflammatory response.
- Treat pulmonary oedema with PEEP or CPAP ventilation.

Dermal Management:

- Remove any remaining contaminated clothing, place in double sealed, clear bags, label

continued...

# CSS MARKER PAINT

## Chemwatch Material Safety Data Sheet

Issue Date: 27-May-2008

NC317ECP

CHEMWATCH 15-6780

Version No:2.0

CD 2008/2 Page 3 of 14

Section 4 - FIRST AID MEASURES

and store in secure area away from patients and staff.

- Irrigate with copious amounts of water.
- An emollient may be required.

Eye Management:

- Irrigate thoroughly with running water or saline for 15 minutes.
- Stain with fluorescein and refer to an ophthalmologist if there is any uptake of the stain.

Oral Management:

- No GASTRIC LAVAGE OR EMETIC
- Encourage oral fluids.

Systemic Management:

- Monitor blood glucose and arterial pH.
- Ventilate if respiratory depression occurs.
- If patient unconscious, monitor renal function.
- Symptomatic and supportive care.

The Chemical Incident Management Handbook:  
Guy's and St. Thomas' Hospital Trust, 2000

### BIOLOGICAL EXPOSURE INDEX

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant	Sampling Time	Index	Comments
Acetone in urine	End of shift	50 mg/L	NS

NS: Non-specific determinant; also observed after exposure to other material.

## Section 5 - FIRE FIGHTING MEASURES

### EXTINGUISHING MEDIA

SMALL FIRE:

- Water spray, dry chemical or CO<sub>2</sub>

LARGE FIRE:

- Water spray or fog.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 100 metres in all directions.

### FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.

continued...

# CSS MARKER PAINT

Chemwatch Material Safety Data Sheet

Issue Date: 27-May-2008

NC317ECP

CHEMWATCH 15-6780

Version No:2.0

CD 2008/2 Page 4 of 14

Section 5 - FIRE FIGHTING MEASURES

---

- Severe fire hazard when exposed to heat or flame.
  - Vapour forms an explosive mixture with air.
  - Severe explosion hazard, in the form of vapour, when exposed to flame or spark.
  - Vapour may travel a considerable distance to source of ignition.
  - Heating may cause expansion or decomposition with violent container rupture.
  - Aerosol cans may explode on exposure to naked flames.
  - Rupturing containers may rocket and scatter burning materials.
  - Hazards may not be restricted to pressure effects.
  - May emit acrid, poisonous or corrosive fumes.
  - On combustion, may emit toxic fumes of carbon monoxide (CO).
- Other combustion products include: carbon dioxide (CO<sub>2</sub>), nitrogen oxides (NO<sub>x</sub>), metal oxides.

## FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM: 2Y

## Personal Protective Equipment

Gas tight chemical resistant suit.

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### EMERGENCY PROCEDURES

#### MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.
- Wipe up.
- If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated.
- Undamaged cans should be gathered and stowed safely.

#### MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Absorb or cover spill with sand, earth, inert materials or vermiculite.
- If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated.
- Undamaged cans should be gathered and stowed safely.
- Collect residues and seal in labelled drums for disposal.

### PROTECTIVE ACTIONS FOR SPILL


continued...

# CSS MARKER PAINT

Chemwatch Material Safety Data Sheet  
Issue Date: 27-May-2008  
NC317ECP

CHEMWATCH 15-6780  
Version No:2.0  
CD 2008/2 Page 5 of 14

## Section 6 - ACCIDENTAL RELEASE MEASURES



From IERG (Canada/Australia)

Isolation Distance	-
Downwind Protection Distance	8 metres
IERG Number	49

### FOOTNOTES

- 1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.
- 2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.
- 3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.
- 4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills".  
LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.
- 5 Guide 126 is taken from the US DOT emergency response guide book.
- 6 IERG information is derived from CANUTEC - Transport Canada.

**Personal Protective Equipment advice is contained in Section 8 of the MSDS.**

## Section 7 - HANDLING AND STORAGE

### PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- DO NOT incinerate or puncture aerosol cans.
- DO NOT spray directly on humans, exposed food or food utensils.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.

continued...

# CSS MARKER PAINT

Chemwatch Material Safety Data Sheet

Issue Date: 27-May-2008

NC317ECP

CHEMWATCH 15-6780

Version No:2.0

CD 2008/2 Page 6 of 14

Section 7 - HANDLING AND STORAGE

- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

## SUITABLE CONTAINER

- Aerosol dispenser.
- Check that containers are clearly labelled.

## STORAGE INCOMPATIBILITY

Avoid storage with oxidisers.

## STORAGE REQUIREMENTS

- Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can.
- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed. Contents under pressure.
- Store away from incompatible materials.
- Store in a cool, dry, well ventilated area.
- Avoid storage at temperatures higher than 40 deg C.
- Store in an upright position.
- Protect containers against physical damage.
- Check regularly for spills and leaks.
- Observe manufacturer's storing and handling recommendations.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>
Australia Exposure Standards	acetone (Acetone)	500	1185	1000	2375
Australia Exposure Standards	hydrocarbon propellant (LPG (liquified petroleum gas))	1000	1800		

The following materials had no OELs on our records

- aromatic hydrocarbons:

CAS:63231- 51- 6

### EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m <sup>3</sup> )	Revised IDLH Value (ppm)
acetone		2, 500 [LEL]
hydrocarbon propellant		2, 000 [LEL]

### NOTES

Values marked LEL indicate that the IDLH was based on 10% of the lower explosive limit for safety considerations even though the relevant toxicological data indicated that irreversible health effects or impairment of escape existed only at higher concentrations.

### MATERIAL DATA

Not available. Refer to individual constituents.

continued...

# CSS MARKER PAINT

Chemwatch Material Safety Data Sheet

Issue Date: 27-May-2008

NC317ECP

CHEMWATCH 15-6780

Version No:2.0

CD 2008/2 Page 7 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

## INGREDIENT DATA

### ACETONE:

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

$OSF = \text{Exposure Standard (TWA) ppm} / \text{Odour Threshold Value (OTV) ppm}$

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

Odour Threshold Value: 3.6 ppm (detection), 699 ppm (recognition)

Saturation vapour concentration: 237000 ppm @ 20 C

NOTE: Detector tubes measuring in excess of 40 ppm, are available.

Exposure at or below the recommended TLV-TWA is thought to protect the worker against mild irritation associated with brief exposures and the bioaccumulation, chronic irritation of the respiratory tract and headaches associated with long-term acetone exposures. The NIOSH REL-TWA is substantially lower and has taken into account slight irritation experienced by volunteer subjects at 300 ppm. Mild irritation to acclimatised workers begins at about 750 ppm - unacclimatised subjects will experience irritation at about 350-500 ppm but acclimatisation can occur rapidly. Disagreement between the peak bodies is based largely on the view by ACGIH that widespread use of acetone, without evidence of significant adverse health effects at higher concentrations, allows acceptance of a higher limit.

Half-life of acetone in blood is 3 hours which means that no adjustment for shift-length has to be made with reference to the standard 8 hour/day, 40 hours per week because body clearance occurs within any shift with low potential for accumulation.

A STEL has been established to prevent excursions of acetone vapours that could cause depression of the central nervous system.

### AROMATIC HYDROCARBONS:

Insufficiently classified, hence a "worst case value" is assumed, viz

CEL TWA: 50 ppm, 150 mg/m<sup>3</sup> as total hydrocarbons

for petroleum distillates:

CEL TWA: 500 ppm, 2000 mg/m<sup>3</sup> (compare OSHA TWA).

continued...

# CSS MARKER PAINT

Chemwatch Material Safety Data Sheet

Issue Date: 27-May-2008

NC317ECP

CHEMWATCH 15-6780

Version No:2.0

CD 2008/2 Page 8 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

## PERSONAL PROTECTION

### EYE

No special equipment for minor exposure i.e. when handling small quantities.

OTHERWISE: For potentially moderate or heavy exposures:

- Safety glasses with side shields.
- NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.

### HANDS/FEET

- No special equipment needed when handling small quantities.
- OTHERWISE:
- For potentially moderate exposures:
- Wear general protective gloves, eg. light weight rubber gloves.
- For potentially heavy exposures:
- Wear chemical protective gloves, eg. PVC. and safety footwear.

### OTHER

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Skin cleansing cream.
- Eyewash unit.
- Do not spray on hot surfaces.

### RESPIRATOR

Respiratory protection may be required when ANY "Worst Case" vapour-phase concentration is exceeded (see Computer Prediction in "Exposure Standards").

Protection Factor (Min)	Half- Face Respirator	Full- face Respirator
10 x ES	AX- - AUS AX- - PAPR- AUS	- -
20 x ES	-	AX- - AUS AX- - PAPR- AUS
100 x ES	-	AX- - 2 AX- - PAPR- 2

^ - Full-face.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

## ENGINEERING CONTROLS

General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection.

Provide adequate ventilation in warehouse or closed storage areas.

---

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

---

### APPEARANCE

Supplied as an aerosol pack. Contents under PRESSURE. Contains highly flammable

continued...

# CSS MARKER PAINT

Chemwatch Material Safety Data Sheet

Issue Date: 27-May-2008

NC317ECP

CHEMWATCH 15-6780

Version No:2.0

CD 2008/2 Page 9 of 14

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

hydrocarbon propellant.

Highly flammable liquid with sweet solvent odour; does not mix with water.

### PHYSICAL PROPERTIES

Liquid.

Gas.

Does not mix with water.

Sinks in water.

Molecular Weight: Not Applicable

Melting Range (°C): - 188 propellant

Solubility in water (g/L): Immiscible

pH (1% solution): Not Available

Volatile Component (%vol): >60

Relative Vapour Density (air=1): >1

Lower Explosive Limit (%): 1.5 propellant

Autoignition Temp (°C): 431 propellant

State: Liquid

Boiling Range (°C): - 20 propellant

Specific Gravity (water=1): 1.32

pH (as supplied): Not Applicable

Vapour Pressure (kPa): 607.96

Evaporation Rate: Fast

Flash Point (°C): - 80 propellant

Upper Explosive Limit (%): 10.0 propellant

Decomposition Temp (°C): Not Available

Viscosity: Not Available

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Elevated temperatures.
- Presence of open flame.
- Product is considered stable.
- Hazardous polymerisation will not occur.

## Section 11 - TOXICOLOGICAL INFORMATION

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

Not normally a hazard due to physical form of product.

Accidental ingestion of the material may be damaging to the health of the individual.

Ingestion may result in nausea, pain, vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

##### EYE

The material may produce severe irritation to the eye causing pronounced inflammation.

Repeated or prolonged exposure to irritants may produce conjunctivitis.

##### SKIN

Skin contact with the material may be harmful; systemic effects may result following absorption.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Open cuts, abraded or irritated skin should not be exposed to this material.

The material may accentuate any pre-existing skin condition.

##### INHALED

Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.

continued...

# CSS MARKER PAINT

Chemwatch Material Safety Data Sheet

Issue Date: 27-May-2008

NC317ECP

CHEMWATCH 15-6780

Version No:2.0

CD 2008/2 Page 10 of 14

## Section 11 - TOXICOLOGICAL INFORMATION

Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.

**WARNING:** Intentional misuse by concentrating/inhaling contents may be lethal.

Inhalation of acetone causes central nervous system depression, light-headedness, incoherent speech, inco-ordination, stupor, low blood pressure, fast pulse, metabolic acidosis, high blood sugar and ketosis. Rarely, convulsions and tubular necrosis may be evident. Other symptoms of exposure may include restlessness, headache, vomiting, low blood pressure and rapid and irregular pulse, eye and throat irritation, weakness of the legs and dizziness. Inhalation of high concentrations may produce dryness of the mouth and throat, nausea, inco-ordinated movement, loss of co-ordinated speech, drowsiness, and in severe cases, coma. Inhalation of acetone vapours over long periods causes irritation of the airways, coughing and headache. Rats exposed to a concentration of 5.22% for 1 hour showed clear signs of sleepiness; deaths occurred at 12.66%.

### CHRONIC HEALTH EFFECTS

Principal routes of exposure are by accidental skin and eye contact and by inhalation of vapours especially at higher temperatures.

Workers exposed to acetone for long periods showed inflammation of the airways, stomach and small bowel, attacks of giddiness and loss of strength. Exposure to acetone may enhance the liver toxicity of chlorinated solvents.

Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS].

### TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

#### ACETONE:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

#### TOXICITY

Oral (man) TDLo: 2857 mg/kg

Oral (rat) LD50: 5800 mg/kg

Inhalation (human) TLo: 500 ppm

Inhalation (man) TLo: 12000 ppm/4 hr

Inhalation (man) TLo: 10 mg/m<sup>3</sup>/6 hr

Inhalation (rat) LC50: 50100 mg/m<sup>3</sup>/8 hr

Dermal (rabbit) LD50: 20000 mg/kg

#### IRRITATION

Eye (human): 500 ppm - Irritant

Eye (rabbit): 3.95 mg - SEVERE

Eye (rabbit): 20mg/24hr - Moderate

Skin (rabbit): 395mg (open) - Mild

Skin (rabbit): 500 mg/24hr - Mild

#### AROMATIC HYDROCARBONS:

NOTE: Insufficient information to identify possible hazards, including the chronic health effects, of this particular substance.

#### HYDROCARBON PROPELLANT:

Not available. Refer to individual constituents.

MATERIAL

CARCINOGEN

REPROTOXIN

SENSITISER

SKIN

aromatic  
hydrocarbons

IARC:3

### CARCINOGEN

IARC: International Agency for Research on Cancer (IARC) Carcinogens: aromatic hydrocarbons Category: The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.

continued...

# CSS MARKER PAINT

Chemwatch Material Safety Data Sheet

Issue Date: 27-May-2008

NC317ECP

CHEMWATCH 15-6780

Version No:2.0

CD 2008/2 Page 11 of 14

## Section 12 - ECOLOGICAL INFORMATION

DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

### ACETONE:

Fish LC50 (96hr.) (mg/l):	8300- 40000
Daphnia magna EC50 (48hr.) (mg/l):	10
log Kow (Prager 1995):	- 0.24
log Kow (Sangster 1997):	- 0.24
log Pow (Verschueren 1983):	- 0.24
BOD5:	122%
ThOD:	72
Half- life Soil - High (hours):	168
Half- life Soil - Low (hours):	24
Half- life Air - High (hours):	2790
Half- life Air - Low (hours):	279
Half- life Surface water - High (hours):	168
Half- life Surface water - Low (hours):	24
Half- life Ground water - High (hours):	336
Half- life Ground water - Low (hours):	48
Aqueous biodegradation - Aerobic - High (hours):	168
Aqueous biodegradation - Aerobic - Low (hours):	24
Aqueous biodegradation - Anaerobic - High (hours):	672
Aqueous biodegradation - Anaerobic - Low (hours):	96
Aqueous biodegradation - Removal secondary treatment - High (hours):	75%
Aqueous biodegradation - Removal secondary treatment - Low (hours):	54%
Aqueous photolysis half- life - High (hours):	270
Photooxidation half- life water - High (hours):	3.97E+06
Photooxidation half- life water - Low (hours):	9.92E+04
Photooxidation half- life air - High (hours):	2790
Photooxidation half- life air - Low (hours):	279

DO NOT discharge into sewer or waterways.

log Kow: -0.24

Half-life (hr) air: 312-1896

Half-life (hr) H<sub>2</sub>O surface water: 20

Henry's atm m<sup>3</sup> /mol: 3.67E-05

BOD 5 if unstated: 0.31-1.76,46-55%

COD: 1.12-2.07

ThOD: 2.2

BCF: 0.69

Toxicity Fish: LC50(96) 5540-13000mg/L

Toxicity invertebrate: cell mult. inhib. 28-7500mg/L

Bioaccumulation: not sig

Nitrif. inhib.: 75% decr. at 840mg/L

Anaerobic effects: sig degrad

Degradation Biological: sig

processes Abiotic: Rxn OH\*, photodissoc

In air, acetone is lost by photolysis and reaction with photochemically produced hydroxyl radicals; the estimated half-life of these combined processes is about 22 days. The relatively long half-life allows acetone to be transported long distances from its emission source.

Acetone is highly soluble and slightly persistent in water, with a half-life of about 20 hours; it is minimally toxic to aquatic life.

Acetone released to soil volatilises although some may leach into the ground where it rapidly biodegrades.

Acetone does not concentrate in the food chain.

continued...

# CSS MARKER PAINT

Chemwatch Material Safety Data Sheet

Issue Date: 27-May-2008

NC317ECP

CHEMWATCH 15-6780

Version No:2.0

CD 2008/2 Page 12 of 14

Section 12 - ECOLOGICAL INFORMATION

Drinking Water Standard: none available.

Soil Guidelines: none available.

Air Quality Standards: none available.

## HYDROCARBON PROPELLANT:

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

Some of the material will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions the material will degrade to water and carbon dioxide, while under anaerobic processes it will produce water, methane and carbon dioxide.

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

Drinking Water Standards:

hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

## Section 13 - DISPOSAL CONSIDERATIONS

- Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- DO NOT incinerate or puncture aerosol cans.
- Bury residues and emptied aerosol cans at an approved site.

## Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE GAS

HAZCHEM: 2Y

UNDG:

Dangerous Goods

2.1

Subrisk:

None

Class:

UN Number:

1950

Packing Group:

None

Shipping Name: AEROSOLS

### Air Transport IATA:

ICAO/IATA Class:

2.1

ICAO/IATA Subrisk:

None

UN/ID Number:

1950

Packing Group:

None

Special provisions:

A145 A153

continued...

# CSS MARKER PAINT

## Chemwatch Material Safety Data Sheet

Issue Date: 27-May-2008

NC317ECP

CHEMWATCH 15-6780

Version No:2.0

CD 2008/2 Page 13 of 14

Section 14 - TRANSPORTATION INFORMATION

Shipping Name: AEROSOLS, FLAMMABLE

### Maritime Transport IMDG:

IMDG Class:	2.1	IMDG Subrisk:	SP63
UN Number:	1950	Packing Group:	None
EMS Number:	F- D, S- U	Special provisions:	63 190 277 327 959
Limited Quantities:	See SP277	Marine Pollutant:	Not Determined

Shipping Name: AEROSOLS

## Section 15 - REGULATORY INFORMATION

### POISONS SCHEDULE: S5

#### REGULATIONS

CSS Marker Paint (CAS: None):  
No regulations applicable

acetone (CAS: 67-64-1) is found on the following regulatory lists;

- Australia Exposure Standards
- Australia Hazardous Substances
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Illicit Drug Reagents/Essential Chemicals - Category III
- Australia Inventory of Chemical Substances (AICS)
- Australia National Pollutant Inventory
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships
- IMO IBC Code Chapter 18: List of products to which the Code does not apply
- IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances
- International Air Transport Association (IATA) Dangerous Goods Regulations
- OECD Representative List of High Production Volume (HPV) Chemicals
- United Nations Convention Against Illicit Traffic in Narcotic Drugs and Psychotropic Substances - Table II
- United Nations List of Precursors and Chemicals Frequently used in the Illicit Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control - Table II

aromatic hydrocarbons (CAS: 63231-51-6) is found on the following regulatory lists;

- Australia Inventory of Chemical Substances (AICS)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- International Agency for Research on Cancer (IARC) Carcinogens
- International Air Transport Association (IATA) Dangerous Goods Regulations
- OSPAR List of Chemicals for Priority Action

hydrocarbon propellant (CAS: 68476-85-7) is found on the following regulatory lists;

- Australia Exposure Standards
- Australia Hazardous Substances
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- International Air Transport Association (IATA) Dangerous Goods Regulations
- OECD Representative List of High Production Volume (HPV) Chemicals

hydrocarbon propellant (CAS: 68476-86-8) is found on the following regulatory lists;

- Australia Hazardous Substances
- Australia Inventory of Chemical Substances (AICS)
- International Air Transport Association (IATA) Dangerous Goods Regulations
- OECD Representative List of High Production Volume (HPV) Chemicals

## Section 16 - OTHER INFORMATION

### INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
hydrocarbon propellant	68476- 85- 7, 68476- 86- 8

### EXPOSURE STANDARD FOR MIXTURES

"Worst Case" computer-aided prediction of vapour components/concentrations:

Composite Exposure Standard for Mixture (TWA) (mg/m<sup>3</sup>): 150 mg/m<sup>3</sup>

If the breathing zone concentration of ANY of the components listed below is exceeded,

"Worst Case" considerations deem the individual to be overexposed.

Component	Breathing Zone ppm	Breathing Zone mg/m <sup>3</sup>	Mixture Conc: (%)
-----------	--------------------	----------------------------------	-------------------

continued...

# CSS MARKER PAINT

Chemwatch Material Safety Data Sheet

Issue Date: 27-May-2008

NC317ECP

CHEMWATCH 15-6780

Version No:2.0

CD 2008/2 Page 14 of 14

Section 16 - OTHER INFORMATION

---

Component	Breathing zone (ppm)	Breathing Zone (mg/m <sup>3</sup> )	Mixture Conc (%)
aromatic hydrocarbons	50.00	150.0000	30.0

Operations which produce a spray/mist or fume/dust, introduce particulates to the breathing zone.

If the breathing zone concentration of ANY of the components listed below is exceeded, "Worst Case" considerations deem the individual to be overexposed.

At the "Composite Exposure Standard for Mixture" (TWA) (mg/m<sup>3</sup>): 150 mg/m<sup>3</sup>

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:  
[www.chemwatch.net/references](http://www.chemwatch.net/references).

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 27-May-2008

Print Date: 27-May-2008