CONCRETE CONSTRUCTION PRECAST/TILT UP/FORMWORK

POINTED TROWELS



WOOD FLOATS



Flextool pointed trowels are produced using high carbon steel to optimise blade flexibility and durability. Flextool pointed trowels are also fitted with a single piece forged aluminium spine for extra strength and blade support. Available in both ProSoft rubber grip and solid moulded plastic handles.

Wood Floats are used for creating a rough non-slip or textured finish on the concrete surface. Used predominately for outdoor areas such as footpaths and other pedestrian traffic applications. Available with ProSoft rubber handle for user comfort.



Material Number	Description
ETADAGGA LINIT	ELV DOINTED TOOMEL 100M V 355

Material Number Description FT4P8002-UNIT FLX WOOD FLOAT 112W X 380L

SQUARE TROWELS



Flextool square trowels are produced using high carbon steel to optimise blade flexibility and durability. Flextool square trowels are also fitted with a single piece forged aluminium spine for extra strength and blade support. Available with ProSoft rubber grip handles in both closed and open style configurations.





Concrete Edger Bull Nose trowels are used to create a smooth finish to slab edges. They produce a curved profile finish on the concrete edge to prevent chipping and damage to the concrete. Available with ProSoft handle for user comfort.

Material Number	Description
FT44008S-UNIT	FLX EDGER 75W X 140L X 19R X 19D
FT47008S-UNIT	FLX EDGER 140W X 200L X 20R X 19D

Material Number Description FT4P1002-UNIT FLX SQUARE TROWEL 120W X 280L FLX SQUARE TROWEL 120W X 280L OPEN GRIP FT41002O-UNIT

STEEL FLOATS



Steel Floats or "Sides Up" trowels as they are sometimes referred to are used for creating a non-slip finish on the concrete surface, also known as a stippled or coved finish. They are also used for trowelling dry shake materials into the top surface of the concrete.

Steel floats produce a finer texture to wood floats and are more durable and longer wearing due to their solid steel blade. Available with ProSoft rubber handle for user comfort.





Flextool Concrete Screeds are made from durable yet lightweight aluminium extrusions. Concrete screeds are used to level the concrete after it has been placed.



Material Number	Description
FT401808-UNIT	FLX SCREED CLAMPED HANDLE 1500MM VIAL
FT401813-UNIT	FLX SCREED CLAMPED HANDLE 3000MM VIAL

Material Number Description

FT42019S-UNIT FLX STEEL FLOAT 150W X 380L

MAGNESIUM FLOATS



All Flextool magnesium floats are produced with a broken-in or curved blade and come standard with a ProSoft rubber grip for user comfort.



Material Number	Description
FT4P2051-UNIT	FLX MAGNESIUM FLOAT 80W X 405L

RAKES



Material Number	Description
FT4CC013-UNIT	FLX CONCRETE RAKE PUSH & PULL

CONCRETE CONSTRUCTION PRECAST/TILT UP/FORMWORK

PRO POINTED FINISHING TROWEL RANGE

OX-P014601 / OX-P014609 / OX-P014665 / OX-P014691 / OX-P014692 / OX-P014693



- Heavy duty aluminium shank
- 'Double hung' OXGRIP handle Also available:
- Trade Pointed Finishing Trowel Range

OX-T017301 / OX-T017309 / OX-T017365 /OX-T017391 / OX-T017392



PRO ALUMINIUM BULL FLOAT 0X-P016606 / 0X-P016609 / 0X-P016612

- Heavy duty structural alloy
- Easy to clean powder coated finish



Also available:

- Pro Aluminium Bull Float • Mill Finish

OX-P016406 / OX-P016409 / OX-P016412 / OX-P016415 / OX-P016418


- Pro Telescopic Poles (OX-P016524/OX-P016550)
- Pro Clip Together Poles (OX-P019020/OX-P019024)

MAGNESIUM FLOAT - OXGRIP HANDLE OX-P017012 / OX-P017016 / OX-P017020

- Heavy duty magnesium blade
- Bevelled ends and rounded corners
- Ergonomic DURAGRIP handle
- Available in 12", 16" and 20" Also available:
- Rounded Ends (OX-P400416)
- Wide Blade (OX-P400517)



ALUMINIUM BULL FLOAT



Round end aluminium bull floats set :

- 1pc aluminium bull float blade with 4 drilled holes
- 3pcs aluminum swaged handles Ø45mmX1830mm (1-3/4"X72")
- 1pc worm gear bracket
- 1pc red plastic box, which is for easy carry of the tools

PRO 100 X 500MM ALUMINIUM CONCRETE RAKE

- 1500mm long handle with soft grip
- Braced for additional strength
- Aluminium construction powder coated



Material Number	Description
OX-P016302	without hook
OX-P016303	with hook

SPRAYER

The Smith Industrial Sprayers are built to withstand harsh chemicals and are targeted towards contractor or construction work with ease of use and durability at their core. Each sprayer is fitted with chemical-resistant seals and brass components specially designed for contact with acetone, xylene, bond breakers, curing compounds and other concrete chemicals.



Flextoo

Material Number	Description
NP700096-UNIT	SPS SPRAYER CONC SS S103E

PRO CLAMPED HANDLE SCREED WITH VIAL 0X-P021312 / OX-P021315 / OX-P021318 / OX-P021321 / 0X-P021324 / OX-P021327 / OX-P021330 / OX-P021336





Also available:

- Pro Clamped Handle Screed Without Vial Range
- Available in 1200mm 3600mm

OX-P021408 / OX-P021412 / OX-P021415 / OX-P021418 / OX-P021421 / OX-P021424 / OX-P021427 / OX-P021430 / OX-P021436

PRO STAINLESS STEEL CONCRETE SPRAYER - 13.2L 0X-P040713

- Flexible heavy duty chemical resistant hose
- Superior lock-on trigger assembly
- Ergonomic pump handle



Also available:

- Pro Backpack Sprayer • 15L (OX-P044715)

WALK-BEHIND POWER TROWELS BN436

- Contoured handle for control and comfort
- Handle are welded tri tube for max strength
- Control cables and wires run inside the handle for protection
- Dual safety stop systems
- Lifting hook as standard





TROWEL MACHINE - FOLDING HANDLE OX-TM24 / OX-TM30

- Rotating ring
- Chrome folding handle
- Genuine certified HONDA engine
- GX160 5.5HP
- 4 Blade 24" (OX-TM24)
- 6 Blade 30" (OX-TM30)



TROWEL MACHINE 36" GX160 5.5HP OX-TM36

- Powerful performance and easy handling
- Genuine certified HONDA engine Also Available:
- GX270 36" 9HP (OX-TM36/9)
- GX160 40" 5.5HP (OX-TM40)
- GX270 40" 9HP (OX-TM40/9)
- GX270 46" 9HP (OX-TM46/9)
- GX390 46" 13HP (OX-TM46/13)



FINISHING BLADES + PAN FLOATS CTKAC1N

A VARIETY OF BLADES AND PAN FLOATS ARE AVAILABLE

- Finishing blades are designed to produce a smooth and polished finish to the concrete surface.
- Pan floats clip onto both finishing or combination blades.







Material Number	Description	
AC28VS	200mm/8"	
AC210VS	250mm/10"	
AC212VS	300mm/12"	
AC215VS	380mm/15"	
AC218VS	60mm/18"	

TROWEL MACHINE BLADES - SET OF 4 OX-T181401 / OX-T181402 / OX-T181403 / OX-T181404 OX-T181405 / OX-T181406 / OX-T181407 / OX-T181408 OX-T181409 / OX-T181410

- Heat treated for better wear





Also Available:

OX

Also Available:
- Set of 5 (OX-T182603/OX-T182607)





Model		BN-MPSCREED
Weight	kg	12.7
Engine Make		Honda
Engine Model		GX35
Max Rated Power	Нр	1.5
Fuel Type		Petrol

EXTRUSION BARS AVAILABLE FROM 1200mm UP TO 4880mm IN LENGTH

54V XR LI-ION BRUSHLESS DUAL HANDLE PADDLE MIXER

DCD240N-XJ



- Standard M14 paddle connection for user prefer paddle
- 160mm centre pull down swirl paddle for quick and consistent mixing
- Equivalent power of a 2000W corded unit
- Slow ramp up and down speeds reduce material spread
- Supplied with 160mm centre pull down swirl paddle for quick and consistent mixing

