

NON-SAG EPOXY MORTAR BINDER (633)

- Grouting and repairs for vertical & overhead surfaces
- Multi-purpose use
- Non-sag consistency
- High mechanical strength



Material Number	Description
E906334	1L
E906332	4L
E906333	20L

HIGH PERFORMANCE GROUT (280S)

- For higher temperature conditions and deeper pours
- Excellent flow
- High mechanical strength



Material Number	Description
E991199	30kg

HIGHWAY PATCH

- Fast drying concrete repair
- Ideal for repairing footpaths, kerbs and cracks
- Fast curing
- High strengths



Material Number	Description
E991605	15kg

CHOCKFAST RED

- Three component high strength, 100% solids, epoxy grouting
- High compressive strength
- Low exotherm, deep pours up to 450mm



Material Number	Description
D11950	94kg

INSTANT GROUT



- Fast setting, cement-based, non-shrink grout
- Rapid strength gain



Material Number	Description
E991609	15kg

SUPAFLOW HF GROUT (HF)



- Free flowing, cement-based grout
- High performance and non-shrink characteristics
- Excellent flow for easy placement



Material Number	Description
E991620	20kg

GENERAL PURPOSE EPOXY MORTAR BINDER (133)



- Multi-purpose use
- Excellent adhesion to wet or dry concrete
- High mechanical strength
- Low viscosity



Material Number	Description
E901333	1L
E901332	4L
E901334	20L

CHOCKFAST ORANGE



- Designed to withstand severe marine and industrial environments
- Non-shrinking
- High impact and compressive strength



Material Number	Description
D11900	3.4kg