

## FOSROC RENDEROC FC

Renderoc FC cementitious fairing coat is designed for application in thin layers up to 3 mm, to produce a fair-faced appearance to concrete surfaces or masonry surfaces in readiness to receive a protective/decorative coating.



Product Code	Description	Size
FC302000-20KG	Renderoc FC 20kg	20KG

## FOSROC RENDEROC HB

Renderoc HB is a lightweight, high build concrete repair mortar for patching small sections in concrete up to 25 MPa. It can be applied to vertical concrete patches 10mm to 80mm deep.



Product Code	Description	Size
FC306095-20KG	Renderoc HB 20kg	15kg

## FOSROC RENDEROC HB40

Renderoc HB40 is a high build repair mortar for localised repair of reinforced concrete up to 45MPa. It meets requirements of EN1504-3 Class R3. It can be applied to vertical concrete patches 10mm to 40mm deep. Suitable for use with Galvashield anode protection systems.



Product Code	Description	Size
FC303030-20KG	Renderoc HB70 20kg	20kg

## FOSROC RENDEROC HB70

Renderoc HB70 is a high build repair mortar for localised repair of reinforced concrete >45MPa. It meets the requirements of EN1504-3 Class R4. It can be applied to vertical concrete patches 10mm up to 40mm deep. Suitable for use with Galvashield anode protection systems.



Product Code	Description	Size
FC303030-20KG	Renderoc HB70 20kg	20kg

## FOSROC RENDEROC LA55

Renderoc LA55 is a high strength, free-flowing micro-concrete reinstatement mortar for form and pour applications up to 200mm thick. It meets the requirements of EN1504-3 Class R4. Suitable for use with Galvashield anode protection systems. It can be applied 50mm - 200mm thick.



Product Code	Description	Size
FC302030-20KG	Renderoc LA55 20kg	20kg

# CONCRETE REPAIR, GROUTS AND PATCHING COMPOUNDS

## FOSROC CONBEXTRA GP



Conbextra GP is a general purpose shrinkage compensated (Class A) cementitious, flowable or trowellable grout for gap thicknesses from 10mm up to 100mm. Conbextra GP has a 28 day compressive strength of 65 MPa when mixed at trowellable consistency.



Product Code	Description	Size
FC501020-20KG	Conbextra GP 20kg	20kg

## FOSROC CONBEXTRA EP65 PLUS



Conbextra EP65 Plus is an ultra high strength (125 MPa), 2 component epoxy grout. It is designed for use as a precision, heavy duty grouting for gaps between 10mm and 100mm.



Product Code	Description	Size
FC524460-11.5L	Conbextra EP65 Plus Base 11.5L	20KG
FC524470-2.5L	Conbextra EP65 Plus Hardener 2.5L	

## FOSROC CONBEXTRA C



Conbextra C is a dual shrinkage compensated, high flow cementitious grout for gap thicknesses from 10mm up to 100mm. Conbextra C can be used as a flowable or trowel applied grout.



Product Code	Description	Size
FC501040-20KG	Conbextra C 20kg	20kg

## CRETE PATCH G2 10051



A fine filled, polymer modified, cementitious mortar, specifically formulated for the repair of damaged concrete, covering jointer plates and similar applications. Crete-Patch G2 requires only the addition of water.

- High build polymer modified light weight repair mortar.
- Repairs requiring high build application up to 100mm for vertical applications.
- For use in building up repairs when non structural repair mortar is required
- 4 hour fire resistant



## FOSROC CONBEXTRA HS



Conbextra HS is a dual shrinkage compensated, high flow cementitious grout used grouting applications where rapid strength gain and high ultimate strength is a pre-requisite. Compressive strength of 26 MPa @ 8 hours and 95 MPa @ 28 days when mixed at flowable consistency.



Product Code	Description	Size
FC502000-20KG	Conbextra HS 20kg	20kg



## NON-SAG EPOXY MORTAR BINDER (633)

- Grouting and repairs for vertical & overhead surfaces
- Multi-purpose use
- Non-sag consistency
- High mechanical strength



Material Number	Description
E906334	1L
E906332	4L
E906333	20L

## HIGH PERFORMANCE GROUT (280S)

- For higher temperature conditions and deeper pours
- Excellent flow
- High mechanical strength



Material Number	Description
E991199	30kg

## HIGHWAY PATCH

- Fast drying concrete repair
- Ideal for repairing footpaths, kerbs and cracks
- Fast curing
- High strengths



Material Number	Description
E991605	15kg

## CHOCKFAST RED

- Three component high strength, 100% solids, epoxy grouting
- High compressive strength
- Low exotherm, deep pours up to 450mm



Material Number	Description
D11950	94kg

## INSTANT GROUT



- Fast setting, cement-based, non-shrink grout
- Rapid strength gain



Material Number	Description
E991609	15kg

## SUPAFLOW HF GROUT (HF)



- Free flowing, cement-based grout
- High performance and non-shrink characteristics
- Excellent flow for easy placement



Material Number	Description
E991620	20kg

## GENERAL PURPOSE EPOXY MORTAR BINDER (133)



- Multi-purpose use
- Excellent adhesion to wet or dry concrete
- High mechanical strength
- Low viscosity



Material Number	Description
E901333	1L
E901332	4L
E901334	20L

## CHOCKFAST ORANGE



- Designed to withstand severe marine and industrial environments
- Non-shrinking
- High impact and compressive strength



Material Number	Description
D11900	3.4kg