

## FOSROC RENDEROC FC

Renderoc FC cementitious fairing coat is designed for application in thin layers up to 3 mm, to produce a fair-faced appearance to concrete surfaces or masonry surfaces in readiness to receive a protective/decorative coating.



Product Code	Description	Size
FC302000-20KG	Renderoc FC 20kg	20KG

## FOSROC RENDEROC HB

Renderoc HB is a lightweight, high build concrete repair mortar for patching small sections in concrete up to 25 MPa. It can be applied to vertical concrete patches 10mm to 80mm deep.



Product Code	Description	Size
FC306095-20KG	Renderoc HB 20kg	15kg

## FOSROC RENDEROC HB40

Renderoc HB40 is a high build repair mortar for localised repair of reinforced concrete up to 45MPa. It meets requirements of EN1504-3 Class R3. It can be applied to vertical concrete patches 10mm to 40mm deep. Suitable for use with Galvashield anode protection systems.



Product Code	Description	Size
FC303030-20KG	Renderoc HB70 20kg	20kg

## FOSROC RENDEROC HB70

Renderoc HB70 is a high build repair mortar for localised repair of reinforced concrete >45MPa. It meets the requirements of EN1504-3 Class R4. It can be applied to vertical concrete patches 10mm up to 40mm deep. Suitable for use with Galvashield anode protection systems.



Product Code	Description	Size
FC303030-20KG	Renderoc HB70 20kg	20kg

## FOSROC RENDEROC LA55

Renderoc LA55 is a high strength, free-flowing micro-concrete reinstatement mortar for form and pour applications up to 200mm thick. It meets the requirements of EN1504-3 Class R4. Suitable for use with Galvashield anode protection systems. It can be applied 50mm - 200mm thick.



Product Code	Description	Size
FC302030-20KG	Renderoc LA55 20kg	20kg