

## S SERIES HOSE REELS



- Quality impact resistant UV stabilised covers for maximum durability
- Detachable steel mounting bracket enables 180° hose reel rotation
- Automatic & positive latching mechanism
- Adjustable hose stop for convenient lead length positioning



| Product No. | Product Description    | Hose Length | Hose ID | Working Pressure | Hose Material       | Cover Colour | Hose Colour | Max. Working Temp. | Reel Inlet BSPT(m) | Hose Outlet BSPT(m) | Weight |
|-------------|------------------------|-------------|---------|------------------|---------------------|--------------|-------------|--------------------|--------------------|---------------------|--------|
| SAW100      | Air & Water Hose Reel  | 16m         | 10mm    | 300psi (20bar)   | PVC                 | Red          | BLUE        | 0°C~60°C           | 3/8"               | 3/8"                | 10kg   |
| SAW200      | Air & Water Hose Reel  | 13m         | 12mm    | 300psi (20bar)   | PVC                 | Red          | BLUE        | 0°C~60°C           | 3/4"               | 3/4"                | 10kg   |
| SW500N      | Water Hose Reel        | 18m         | 12mm    | 180psi (20bar)   | Polyurethane        | Blue         | RED         | -20°C~60°C         | 1/2"               | 1/2"                | 10kg   |
| S01700      | Oil Hose Reel          | 10m         | 12mm    | 2,000psi (20bar) | S.A.E. 100R1 Rubber | Black        | BLACK       | -30°C~100°C        | 1/2"               | 1/2"                | 15.6kg |
| SGRW510     | Garden Water Hose Reel | 16m         | 12mm    | 145psi (20bar)   | PVC                 | Green        | GREEN       | 0°C~60°C           | 3/4"               | Nozzle              | 10kg   |

### SAMOA 3/4" SPRING REWIND FUEL, OIL, AIR & WATER HOSE REEL 505224N



- Heavy duty full metal double pedestal construction
- Hose capacity 15m x 19mm ID
- Hose pressure rating 1,500psi (103bar)
- 3/4" BSP(f) inlet/outlet
- Seven position outlet arm



- **505232** Also available SAMOA Spring Rewind Hose Reel - 20m x 12mm ID

### ALEMLUBE EL SERIES WATER HOSE REEL HR40050



- High quality impact & UV resistant polypropylene covers
- 3/4" BSP inlet/outlet
- Maximum working pressure of 300psi (20bar)
- Supplied complete with 20m x 12mm ID PVC hose & 1.2m lead in hose
- Can be wall or ceiling mounted



### ALEMITE LARGE CAPACITY OIL AND FUEL HOSE REEL 8080-G



- Sealed spring cassette
- Suitable for use with air, water, oil & fuel
- Sealed & plated bearings
- 1,000psi (60bar) hose pressure rating
- Narrow width
- Easy and quick mounting
- Supplied complete with 15m x 1" ID hose



- **8080-F** Also available with 25m x 19mm ID hose

### ALEMLUBE EL SERIES AIR, WATER & FUEL SPRING REWIND HOSE REEL HR90040



- Reinforced steel frame provides maximum strength & stability
- Includes 30m x 12mm ID rubber hose & hose stop

- **HR90040** 30m x 1/2" ID hose
- **HR90045** 25m x 1/2" ID hose
- **HR90025** 20m x 3/4" ID hose
- **HR90005** 30m x 1" ID hose
- **HR90015** 8m x 1" ID hose



### ALEMLUBE EL SERIES HOT WATER HOSE REEL WITH NOZZLE HR30070C



- 3/8" BSP inlet/outlet
- 1/2" BSP(m) outlet
- Maximum working pressure of 300psi (20bar)
- Supplied complete with 20m x 10mm ID hybrid polymer hose & 1.9m lead in hose
- High quality impact & UV resistant polypropylene covers



### 1" MECHANICAL DIESEL FUEL METER 51008



- Accurate between flow rates of 20L/min & 120L/min
- Maximum working pressure of 142psi (10bar)
- 1" BSP(f) inlet/outlet ports
- Suitable for gravity feed or pump applications

- **51007** Also available 4-digit meter version

