

ROTARY ACTION DRUM PUMP 501A

- Suitable for the transfer of diesel, petrols, kerosene, lube oil & machine oil
- Delivery rates of up to 18L/min or 0.26L per rotation
- Length: 1,300mm (4.3ft)
- Delivery tube: 31.8mm (1") OD
- Includes 2.2m of farm tank hose, bung adaptor, rubber gasket, a four chamber rotor assembly, spout & spout holster



Alemlube

HEAVY DUTY HI-FLO REFUELLING DRUM PUMP 5060AN

- Delivery rates of 1.1 litres per rotation
- Supplied complete with 2.6m of UV & fuel resistant hose, spout, in built spout holster, 3-piece downtube, bung adaptor
- 3-piece downtube suits 60L & 205L drums and IBC's
- Suitable for the transfer of diesel fuel, petrol, light oils up to SAE30 & kerosene



Alemlube

1" AUTOMATIC DIESEL NOZZLE 51039

- Automatically cuts off when fuel tank is full
- Can operate with flow rates of up to 120L/min
- 1" BSP(f) swivel included
- Suitable for applications involving an electric diesel transfer pump
- **51039P** Also available but for petrol



Alemlube

IN LINE ELECTRONIC FUEL METER 407010N2

- Turbine type meter with aluminium body & polypropylene turbine
- Accurate flow rates of 20 to 120L/min
- Field calibration is possible
- Maximum operating pressure of 290psi (20 bar)
- 6-digit total from 1 to 999,999
- Also suitable for use with diesel, antifreeze & kerosene



Alemlube

LOCKABLE DIESEL REFUELLING STORAGE & DISPENSING KITS

- Flow rates of up to 50L/min
- Heavy duty, robustly constructed polyethylene tank
- Built in nozzle holster
- Unique user friendly design with lockable lid to aid fuel & dispensing kit security
- Dispensing kit consists of a 12V pump, 4m antistatic fuel delivery hose, 2m battery cables & automatic nozzle
- Recesses for tie down straps aid handling
- Forklift lift points
- Suitable for diesel fuel only

Product No.	Capacity	Flow Rate	Meter
L60040PAM	600L	50L/min	Yes
L60040PA	600L	50L/min	No
L45040PAM	450L	50L/min	Yes
L45040PA	450L	50L/min	No
L20040PAM	200L	50L/min	Yes
L20040PA	200L	50L/min	No
L10040PAM	100L	50L/min	Yes
L10040PA	100L	50L/min	No



Alemlube

1L BRAKE CLEANER SPRAYER 6603A

- Large filling opening
- Safety valve at 36psi (2.5bar) with depressurisation option
- Easy tool free maintenance
- Strong translucent bottle with level indicator
- Ergonomic design
- Not suitable for use with acids



Alemlube

20L GEAR OIL DRUM PUMP 8828N2

- Capable of delivering up to 110mL per stroke
- Ideal pump for the transfer of engine, gear, diff & hydraulic oils
- Drainback nozzle holster ensures that excess oil ends up back in the drum
- Drain back holster filter protects against foreign particle contamination
- **7710B** Also available suits 10L drum



Alemlube

12V DIESEL REFUELLING TANK KIT
52000



- Flow rates of up to 50L/min
- Includes 4m of antistatic fuel delivery hose, 2m of battery cable, a stainless steel & brass fuel filter and a manual nozzle
- Maximum head capacity of 15m
- Suction capacity of up to 2m

- 52001 as above but 24V



HIGH VOLUME DIESEL FUEL TRANSFER PUMP
326000



- Flow rates of up to 100L/min
- Vane type pump with sintered steel rotor and acetylic resin vanes
- 1" BSP inlet/outlet
- 240V continuous running operation
- Thermal motor overload protection
- Sturdy cast iron construction
- Suitable for the transfer of diesel fuel



12V HIGH VOLUME AUTO DIESEL PUMP
52004A



- Flow rates of up to 80L/min
- Telescopic down tube suits fuel tanks up to 1,000mm deep
- Includes an automatic shut off nozzle
- Total maximum discharge lift capacity of 10m
- 1" BSP(f) inlet/outlet
- Suitable for diesel fuel transfer only



12V PETROL & AVGAS DRUM PUMP
372010



- Suitable for the transfers of ULP, Avgas, E10, diesel & kerosene
- Automatic nozzle with flow rates of up to 50L/min
- Inbuilt nozzle holster
- 4m long antistatic fuel hose
- Fully-flanged components: pump, flow meter & filters easily fitted or replaced



FUEL TANK FILTER
FA2



- Fuel filter suitable for use with gravity feed fuel tanks & with hand, air or electric drum pumps
- Features a 10 micron fuel filter element, a drain cock & a replaceable clear plastic bowl
- 1" BSP(f) inlet/outlet
- Replacement elements readily available



20LTR PETROL CONTAINER
29106



- AS/NZS 2906 approved
- Flexible vented spout for accessing hard to reach areas
- Dual pour for quick filling
- Accelerated flow by opening opposite cap
- Australian made
- 20ltr pour fast
- Is a non corrosive container



20LTR DIESEL CONTAINER
29107



- AS/NZS 2906 approved
- Flexible vented spout for accessing hard to reach areas
- Dual pour for quick filling
- Accelerated flow by opening opposite cap
- Australian made
- 20ltr pour fast
- Is a non corrosive container



5LTR PLASTIC PRESSURE PACK SPRAYER
11272



- Manual pump action to pressurise.
- Has a release valve to release pressure.
- Lockable trigger for continuous spraying.
- Wide mouth for easy filling.
- Viton seals



FUNNEL SET - 3 PCE
29111



- Stacks for easy storage
- Lightweight and durable
- Diameters: 150mm, 200mm and 250mm
- 30mm – 35mm High side wall for fluid stability
- Wide opening for quick filling
- Made from strong polypropylene material
- Suitable for fuel, oils, coolants and other liquids

