FLUID TRANSFER

SELF-PRIMING INOX SERIES MULTISTAGE PUMP & Controller CLA INOX240A (807724)

Max Flow Rate (L/min): 100 Max Head (m): 48 Power Absorbed (w) P2: 750 Max Suction Lift (m): 4 Inlet Size (mm): 25 Outlet Size (mm): 25 Weight (kg): 12



SUBMERSIBLE LIGHT CONSTRUCTION **PUMP WITH FLOAT**

CLA BLUESUB10 (808366)

ClayTech

ClayTech

ClayTech

kPa: 180 Kilo Watts: 0.75

Max Head (m): 18 Port Size Outlet (BSPF): 2" Particle Size (mm): 10

Volts: 240



ClayTech

ClayTech

9M 250 WATT HEAD DRAINAGE PUMP CLA PROSUB C9 (807695)

Max Flow Rate (L/min): 195 Max Head (m): 9 Power Absorbed (w) P2: 250 Max Solids Handling (mm): 5
Outlet Size (mm): 32
Pump Diameter (mm): 215 Height (mm): 320 Cable Length (m): 10





SUBMERSIBLE IN TANK PRESSURE PUMP CLA DIVERTRON C6 (807685)

Max Flow Rate (L/min): 95 Max Head (m): 36 Power Absorbed (w) P2: 650 Outlet Size (mm): 25 Weight (kg): 10



ECOVORT7 SUBMERSIBLE DRAINAGE PUMP CLA ECOVORT 7 (807699)

Power Absorbed (w): 180 Max Head (m): 7 Pump Max Flow Rate (L/min): 135

Pump Outlet Size: 11/4"

Cable Length (m): 10 Max Solids Handling (mm): 15



HEAVY DUTY SUBMERSIBLE PUMP WITH FLOAT DAB FEKAVS750MA (701560)

Suitable For: Dirty Water Flow Rate (L/min): 400

HP: 1 Kilo Watts: 0.75

Max Head (m): 9.6 Port Size Outlet: 2" BSPF

Particle Size (mm): 50 mm





ENGINE DRIVE PUMPS



WATER TRANSFER & TRASH PUMPS

Full range of 1" to 6" Wanter Transfer and trash pumps available with petrol and diesel options for the entire range.



HIGH PRESSURE FIRE PUMPS

Full range of 1" to 3" High Pressure Fire Pumps available with petrol and diesel options for the entire range.



HIGH PRESSURE FIRE TANKS & SYSTEMS

Extensive range of water tanks and complete fire systems that can be tailored to your requirements.


PUMPS BN228



- Standard flexshaft
- Aluminium pump body for improved portability
- 3 Dog drive coupling
- 6m flexshaft available APPLICATIONS
- Excavations pits
- Construction sites
- Pier holes
- Dams



SINGLE IMPELLER ENGINE DRIVEN FIRE PUMP CLA HP15ABS (808368)



Hp: 6.5 Max Flow (L/min): 330 Max Head (m): 55

Port Size Outlet: 1 x 1-1/2" +

2 x 1"BSPM



TWIN IMPELLER ENGINE DRIVEN FIRE PUMP CLA 2HP15ABS (808369)



Fuel: Petrol

HP: 6.5 Max Flow (L/min): 300

Max Head (m): 80

Port Size Outlet: 1 x 1-1/2" +

2 x 1"BSPM



ENGINE DRIVEN TRANSFER PUMP CLA WP15 (808367)

Suitable For: Water Transfer Fuel: Petrol

HP: 3.0 Max Flow (L/min): 300 Max Head (m): 25

Port Size Outlet: 1-1/2" BSPM



ENGINE DRIVEN FIRE PUMP POWERED BY HONDA GX160

BIA-MH15SHP (809993)

Suitable For: Water Transfer

Fuel: Petrol Hp: 4.8 Max Flow (L/min): 390

Max Head (m): 74.5 Port Size Outlet: 1 x 1-1/2" +

2 x 1"BSPM







ClayTech

