MATERIALS HANDLING / WHEELS AND CASTORS

BEAVER SHACKLE BOW GRADE S GALV

- Complies to AS2741

Product Code	Size (mm)	WLL (t)
242305	5 x 6	0.33
242306	6 x 8	0.5
242308	8 x 10	0.75
242310	10 x 11	1
242311	11 x 13	1.5
242313	13 x 16	2
242316	16 x 19	3.2
242319	19 x 22	4.7
242322	22 x 25	6.5
242325	25 x 29	8.5



AUSTLIFT

AUSTLIFT

BEAVER SHACKLE BOW GRADE S

- Alloy grade S shackles
- Colour Coded painted finish
- Suitable for mining, resource, and construction applications





AUSTLIFT

- Complies to AS2741

Product Code	Size (mm)	WLL (t)	Colour
242310M	10 x 11	1	Violet
242313M	13 x 16	2	Green
242316M	16 x 19	3.2	Yellow
242319M	19 x 22	4.7	Grey
242322M	22 x 25	6.5	Brown
242325M	5 x 29	8.5	Blue

GRADE S SHACKLE BOW TYPE, SCREW PIN

- Proof tested to 2 x working load limit
- With a minimum break force of 6 x WLL

Code	Size	WLL
503006	6mm	0.5T
503013	13mm	2.0T



GRADE S SHACKLE DEE TYPE, SCREW PIN

- Proof tested to 2 x working load limit
- With a minimum break force of 6 x WLL

Code	Size	WLL
504011	11mm	1.5T
504013	13mm	2.0T



GRADE 80 WELD ON LIFTING POINT 1T - 8T

Code	WLL
104001	1T
104003	3T



BEAVER SAFETY CARGO NET NETSYS

- Sizes: S (2.46m X 2.46m),
 M (2.8m x 2.84m), L (2.8m X 3.44m)
- Multiple webbing loops and eyelets
- 4x Tie Ropes and 4x Cam Buckles
- UV stabilised and tightly woven meshIntegrated D rings to assist holding down
- For trailers, utes, boats, 4WD's and trucks
- Convenient heavy duty storage bag



BEAVER WELD-ON RING BALPVO

- Sizes: 1.5, 2.5t, 4t, 6.7t
- Extremely high strength attachment as a lifting and lashing point
- Easily welded into required position with the aid of height lugs on the weld block
- Functional compact design
- Lifting ring has durable powder coated baked enamel finish



PUNCTURE PROOF WHEEL 390MM

- Puncture proof wheel 390mm
- Axle diameter 25mm
- Common bearing
- 150kg capacity
- Great to use on building sites
- Available in two widths 90mm and 130mm





IMPACT-

Code	Description
28905	Standard - 390mm x 90mm
28906	Extra Wide - 390mm x 130mm

PNUEMATIC WHEEL 28904

- 390mm x 130mm
- Axle diameter 25mm
- Common bearing
- 150kg capacity.





