

STEEL FRAMING



GRIPSHANK™ SUPERSHARPY™

1060 CARBON STEEL



Part No.	Description	mm	mm	mm	mm	qty	qty
SNC2359NG	Gripshank™ Supersharpy™ 38x2.5	0.4 - 2.5	38	2.5	6.4	1000	4000
SNC2509NG	Gripshank™ Supersharpy™ 50x2.5	0.4 - 2.5	50	2.5	6.4	800	3200
SNC2639NG	Gripshank™ Supersharpy™ 63x2.5	0.4 - 2.5	63	2.5	6.4	600	2400



TRIM 15 GAUGE HARDENED BRADS



Part No.	Description	mm	mm	gauge	qty	qty
SNS075-100T	Trim Brad 25x15g	0.4 - 3.0	25	15g	3000	30,000
SNS075-150T	Trim Brad 38x15g	0.4 - 3.0	38	15g	1500	15,000
SNS1200 Finish	Trim Brad 50x15g	0.4 - 3.0	50	15g	1500	15,000

Note: 15 Gauge = 15 Pins per inch



STEEL CHASSIS PIN

1060 CARBON STEEL



Part No.	Description	mm	mm	mm	mm	qty	qty
SNS5454PG	Twist Shank Pin with PT2000® Coating	0.9-4.0mm	45	3.6	7.6	3200	n/a



GRIPSHANK™ SUPERSHARPY™

1060 CARBON STEEL



Part No.	Description	mm	mm	mm	qty	qty
SNS2229DG	2.9 x 22mm Breakaway Nail Strip	22	2.9	6.4	1000	5000
SNS3829DG	2.9 x 38mm Breakaway Nail Strip	38	2.9	6.4	1000	5000



Cooperage Pin

1060 CARBON STEEL



Part No.	Description	mm	mm	mm	qty	qty
SNFP012C	2.8 x 13mm Cooperage Breakaway Nail Strip	13	2.8	6.4	5000	n/a



Gas Tool



Fuel Cell



Metal Washer



Magnetic Adaptor



Part No.	Description	qty	qty
SNTST3025C	Gas Pin Nailer for Breakaway Strip Pins	1	n/a
GT-IXF-24+	Gas GT Fuel Cell only	1	12
GTW25	25mm O.D. Metal Washer (use with GTMA-25W)	250	5000
GTMA-25W	Magnetic Adaptor for use with 25mm O.D. Metal Washer (suitable for GT-6 & GT-3 Tools)	1	n/a

PASLODE POWERMASTER PF350-S STRIP NAILER

CODE B20430

Powerful - easily drives through hardwood



Accessories

B20432	Hanger Bracket
F27625	Lubricating Oil
219228	No Mar Tip (for use with decking and cladding)
B20544L	Degreaser

Fastener Specifications

Fastener type	Paslode JDN
Collation angle	34 degrees
Shank diameters	2.87 - 3.15mm
Shank types	Smooth & Ring
Shank lengths	50mm - 90mm
Finishes	Bright, Hot Dip Galvanised

Tool Specifications

Weight	3.5kg
Length	495mm
Height	345mm
Operating Pressure	80psi - 120psi
Magazine capacity	84 nails approx.

Applications

- Framing • Flooring • Roofing • Eaves
- Trusses • Joists • Decking • Cladding

Fasteners

NAIL PACKS

PRODUCT CODE	LENGTH X DIAMETER	SHANK TYPE	FINISH	QTY
B20463	50mm x 2.87mm	Smooth	Bright	3,000
B20528D	50mm x 2.87mm	Smooth	Hot Dipped Galv	3,000
B20465	65mm x 2.87mm	Smooth	Bright	3,000
B20529	65mm x 2.87mm	Smooth	Hot Dipped Galv	3,000
B20531	65mm x 2.87mm	Ring	Bright	3,000
B20539	75mm x 3.06mm	Ring	Bright	3,000
B20467	75mm x 3.06mm	Smooth	Bright	3,000
B20529D	75mm x 3.06mm	Smooth	Hot Dipped Galv	3,000
B20469	90mm x 3.15mm	Smooth	Bright	3,000
B20529F	90mm x 3.15mm	Smooth	Hot Dipped Galv	3,000

PASLODE CNW70.2 COIL NAILER

CODE B21095

Powerful - easily drives through hardwood

Toolfree Depth Set - easily adjusts for flush or deep drive

Dual Fastener Range - accepts wire and plastic coil nails



Tool Specifications

Weight	2.85kg
Length	272mm
Height	323mm
Operating Pressure	70psi - 110psi
Fastener capacity	250 nails approx.

Fastener Specifications

Fastener type	Paslode plastic sheet & wire coil nails
Collation angle	15 degrees
Shank diameters	2.5mm - 2.8mm
Shank types	Smooth, Ring, Screw
Shank lengths	32mm - 70mm
Finishes	Bright, Electro Galvanised, Hot Dipped Galvanised, Stainless Steel

Accessories

F27625	Pneumatic Oil
--------	---------------

Applications

- Decking
- Cladding
- Fencing
- Ply bracing
- Flooring
- Metal connectors
(Trip-L grips etc.)

Fasteners

PLASTIC COLLATION

PRODUCT CODE	LENGTH X DIAMETER	SHANK TYPE	FINISH	QTY
B25110*	32mm x 2.5mm	Screw	Electro Galv	3,600
B25115	32mm x 2.7mm	Smooth	Hot Dipped Galv	3,600
B25120	32mm x 2.7mm	Ring	Hot Dipped Galv	3,600
B25135	45mm x 2.5mm	Ring	Hot Dipped Galv	1,800
B25140	50mm x 2.5mm	Ring	Hot Dipped Galv	1,800
B25145	50mm x 2.5mm	Ring	Stainless Steel	1,800
B25150	50mm x 2.5mm	Screw	Stainless Steel	1,800
B25155*	52mm x 2.5mm	Ring	Hot Dipped Galv	1,800
B25160*	52mm x 2.5mm	Ring	Stainless Steel	1,800
B25165*	52mm x 2.5mm	Screw	Hot Dipped Galv	1,800
B25170*	52mm x 2.5mm	Screw	Stainless Steel	1,800
B25175	60mm x 2.5mm	Smooth	Hot Dipped Galv	1,800
B25180*	60mm x 2.7mm	Ring	Hot Dipped Galv	1,800
B25185*	60mm x 2.7mm	Ring	Stainless Steel	1,800
B25195*	60mm x 2.7mm	Screw	Stainless Steel	1,800

* Dome Head Nails • Hardened