SCREWS AND AUTO-FEED SCREW SYSTEMS

VORTEX™ CYCLONE

BREMICK

UNIVERSAL CYCLONE ASSEMBLY FOR STEEL & TIMBER



The Bremick Vortex[™] Cyclone is a preassembled Universal Cyclone Assembly complete with a marine grade Aluminium/ EPDM "BRA" Cyclone washer, suitable for use with all corrugated and square rib roofing profiles which is mounted on the Vortex[™] self drilling screw, designed for universal application into Timber, Metal Battens and Steel purlins up to 2mm thick.* Available in 25mm, 55mm, 65mm and 95mm.

Available in galvanised and B8 finishes.

Heavy Duty BRA Washer

- Marine Grade Aluminium
- EPDM Extruded Seal
- · Non conductive

Vortex[™] Thread

- 4 Sealing points
- TopGrip™
 - Maintains sealing pressure
- in timber and steel. Universal Drill Point • Timber, metal battens,

· For optimum performance

- Steel purlins
 Tested & Certified to:
 - BCA Spec B 1.2 AS 4040 • AS 1562.1
- NT Deemed To Comply

Product	Features	QTY	Pack	Code
M6.2-13 x 25	CL4+, W	250	Bulk	SUHC462025D
	B8(CAT5),W	250	Bulk	SUHC862025D
M6.2-13 x 55	CL4+, TG, W	250	Bulk	SUHC462055D
	B8(CAT5), TG, W	250	Bulk	SUHC862055D
M6.2-13 x 65	CL4+, TG, W	250	Bulk	SUHC462065D
	B8(CAT5),TG,W	250	Bulk	SUHC862065D
M6.2-13 x 95	CL4+, TG, W	250	Bulk	SUHC462095D

POLYCARBONATE ASSEMBLY FOR TIMBER

VORTEX[™] POLY



One Step fastening of corrugated and square rib sheeting. Ideal for profile rib heights 16mm to 29mm. Cutting fins automatically form expansion hole and self centre screw during installation. Vortex[™] universal screw for timber or steel up to 1.5mm thick. Armour Coat[™] protection to AS 3566 Class 4. 26mm diameter EPDM sealing washer for water tight seal. Available in 50mm and 65mm length.



One Step fastening of corrugated and square rib sheeting. Suitable for profile rib heights 16mm to 35mm into steel purlins up to 2.4mm. Cutting fins automatically form expansion hole and self centre screw. Armour Coat[™] protection. Weather seal sealing washer for water tight and secure fastening. Hi Visibility seal highlights non trafficable sky light zones. Available in 65mm length.

VORTEX[™] ROOF



Br=Mick[®]

UNIVERSAL ROOFING SCREW FOR STEEL & TIMBER



Increases drill drive speed. Provides faster installation by reducing torque. Eight times harder than conventional

Class 4 coatings. Fully compatible with COLORBOND® Ultra Steel, ZINCALUME®, COLORBOND® and Galvanized and Zinc coated products. Suitable for use in ACQ and CCQ treated timber. Available in 50mm and 65mm length.

Available in galvanised and B8 finishes.

ONE SHOT™ POLYCARBONATE SCREWS

DEWALT



Material Number	Description
SDPOSC41260100-PWR	860 - Sd Powers Oneshot C4 12X60 100Pk
SDPOSC41260500-PWR	861 - Sd Powers Oneshot C4 12X60 500Pk
T17POSC412501H-PWR	870 - T17 Powers Oneshot C4 12X50 100Pk
T17POSC412505H-PWR	871 - T17 Powers Oneshot C4 12X50 500Pk
T17POSC412651H-PWR	872 - T17 Powers Oneshot C4 12X65 100Pk
T17POSC412655H-PWR	873 - T17 Powers Oneshot C4 12X65 500



fixing & coarse thread for timber fixing. This screw has shank protection and excellent holding power. Available in class 4 galvanised head or Colorbond* painted head. *Colorbond is a registered

trademark of BlueScope Steel Ltd.

MULTIPURPOSE SELF DRILLING SCREW

The Macsim Self Drilling Screws are designed to drill through mild and structural steel. No pre-drilling required. Available in a range of head types and finishes.

HEAD	FINISH	LENGTH
Hex	YZP, Gal, SS	Various
Button	YZP, Climogard	12mm-30mm
Wafer	YZP, Climogard, SS	16mm-40mm
Bugle	YZP, Climogard	25mm-75mm
Csk.	YZP, Climogard, SS	16mm-65mm
Self Embed.	YZP, Climogard	20mm-40mm
Pan	YZP, Climogard, SS	12mm-25mm



MACSIM° 🕥

CSK RIBBED WITH WINGS SQUARE DRIVE T9PG3RQ







- Metal - Class 3

SELF DRILLING SCREW HEX FLANGE

- Imperial - SS 304



SELF DRILLING SCREW WAFER PHILLIPS

- Imperial - SS 304



SELF DRILLING SCREW CSK PHILLIPS

- Imperial - SS 304

- Imperial

- SS 304







