# **MURO - AUTO FEED - COLLATED SCREWS**





## **MURO - AUTO FEED - COLLATED SCREWS**





**VORTEX™ CYCLONE** 



### **VORTEX<sup>™</sup> POLY**



### **UNIVERSAL CYCLONE ASSEMBLY FOR STEEL & TIMBER**



The Bremick Vortex™ Cyclone is a preassembled Universal Cyclone Assembly complete with a marine grade Aluminium/ EPDM "BRA" Cyclone washer, suitable for use with all corrugated and square rib roofing profiles which is mounted on the Vortex<sup>™</sup> self drilling screw, designed for universal application into Timber, Metal Battens and Steel purlins up to 2mm thick.\* Available in 25mm, 55mm, 65mm and 95mm.

### Available in galvanised and B8 finishes.

### **Heavy Duty BRA Washer**

- · Marine Grade Aluminium
- · EPDM Extruded Seal
- · Non conductive
- · 4 Sealing points

### **TopGrip™**

- · Maintains sealing pressure
- Vortex<sup>™</sup> Thread

· For optimum performance in timber and steel.

### **Universal Drill Point**

· Timber, metal battens, Steel purlins

### Tested & Certified to:

- BCA Spec B 1.2 AS 4040 · AS 1562.1
- · NT Deemed To Comply

Product	Features	QTY	Pack	Code
M6.2-13 x 25	CL4+, W	250	Bulk	SUHC462025D
	B8(CAT5),W	250	Bulk	SUHC862025D
M6.2-13 x 55	CL4+, TG, W	250	Bulk	SUHC462055D
	B8(CAT5), TG, W	250	Bulk	SUHC862055D
M6.2-13 x 65	CL4+, TG, W	250	Bulk	SUHC462065D
	B8(CAT5),TG,W	250	Bulk	SUHC862065D
M6.2-13 x 95	CL4+, TG, W	250	Bulk	SUHC462095D

### POLYCARBONATE ASSEMBLY FOR TIMBER



One Step fastening of corrugated and square rib sheeting. Ideal for profile rib heights 16mm to 29mm. Cutting fins automatically form expansion hole and self centre screw during installation. Vortex<sup>™</sup> universal screw for timber or steel up to 1.5mm thick. Armour Coat™ protection to AS 3566 Class 4. 26mm diameter EPDM sealing washer for water tight seal. Available in 50mm and 65mm length.

**VORTEX™ FIBREGLASS** 





One Step fastening of corrugated and square rib sheeting. Suitable for profile rib heights 16mm to 35mm into steel purlins up to 2.4mm. Cutting fins automatically form expansion hole and self centre screw. Armour Coat™ protection. Weather seal sealing washer for water tight and secure fastening. Hi Visibility seal highlights non trafficable sky light zones. Available in 65mm length.

VORTEX<sup>™</sup> ROOF



### **UNIVERSAL ROOFING SCREW FOR STEEL & TIMBER**





Increases drill drive speed. Provides faster installation by reducing torque. Eight times harder than conventional Class 4 coatings. Fully compatible with COLORBOND® Ultra Steel, ZINCALUME®, COLORBOND® and Galvanized and Zinc coated products. Suitable for use in ACQ and CCQ treated timber. Available in 50mm and 65mm length.

Available in galvanised and B8 finishes.

### ONE SHOT™ POLYCARBONATE SCREWS





Material Number	Description
SDPOSC41260100-PWR	860 - Sd Powers Oneshot C4 12X60 100Pk
SDPOSC41260500-PWR	861 - Sd Powers Oneshot C4 12X60 500Pk
T17POSC412501H-PWR	870 - T17 Powers Oneshot C4 12X50 100Pk
T17POSC412505H-PWR	871 - T17 Powers Oneshot C4 12X50 500Pk
T17POSC412651H-PWR	872 - T17 Powers Oneshot C4 12X65 100Pk
T17POSC412655H-PWR	873 - T17 Powers Oneshot C4 12X65 500

### **MULTIPURPOSE SELF DRILLING SCREW**

MACSIM® 🗐

The Macsim Self Drilling Screws are designed to drill through mild and structural steel. No pre-drilling required. Available in a range of head types and finishes.

HEAD	FINISH	LENGTH
Hex	YZP, Gal, SS	Various
Button	YZP, Climogard	12mm-30mm
Wafer	YZP, Climogard, SS	16mm-40mm
Bugle	YZP, Climogard	25mm-75mm
Csk.	YZP, Climogard, SS	16mm-65mm
Self Embed.	YZP, Climogard	20mm-40mm
Pan	YZP, Climogard, SS	12mm-25mm

### **CSK RIBBED WITH WINGS SQUARE DRIVE** T9PG3RQ

**REDUCED HEX HEAD FLANGE** 





- Metal
- Class 3

T9PM3RH

- Metal - Class 3



# HEX HEAD FLANGE WITH SEAL T9PM4XS





- Scratchguard®



# **HEX HEAD WITH MULTISEAL**


T9PM4YM

- Cyclone
- Metal
- Class 4





### **VMAX® HEX HEAD FLANGE WITH SEAL** T9PV4XS













## **SELF DRILLING SCREW HEX FLANGE**



- SS 304



### **BI-FIX™ HEX HEAD WITH ALUMINIUM SEAL**

T4XMXAH



- SS 304







### **SELF DRILLING SCREW WAFER PHILLIPS**

- Imperial - SS 304





# **SELF DRILLING SCREW CSK PHILLIPS**

MACSIM® @

- Imperial

- SS 304





## **TORNADO SCREWS**

A registered dual fine and coarse thread screw. Fine thread for metal batten fixing & coarse thread for timber fixing. This screw has shank protection and excellent holding power. Available in class 4 galvanised head or Colorbond\* painted head. \*Colorbond is a registered trademark of BlueScope Steel Ltd.



### **SELF DRILLING SCREW PAN PHILLIPS**

- Imperial
- SS 304







# **SCREWS AND AUTO-FEED SCREW SYSTEMS**

### **WAFER HEAD PHILLIPS** T9P53WP







- s500
- Class 3



### FLOWER HEAD SELF EMBED **PHILLIPS Т9РМҮОР**





- Metal
- Zinc Yellow Passivated



# PAN HEAD TRILOBULAR DRIVE





- Metal


- Class 3





## **DRYWALL SCREWS**

Drywall Screws are specialised self tapping screws, designed to attach drywall to timber or metal studs.



**HEX FLANGE SCREW W & WO/NEO T17** 

# macsim<sup>®</sup>



### **SELF TAPPING SCREWS**

Macsim Self Tapping SCrews can be used in steel or timber. They are available in zinc plated, stainless steel with a pan or countersunk head.

HEAD	FINISH	LENGTH
Csk.	Zinc Plated	6mm-50mm
	304 Stainless Steel	13mm-65mm
Pan	Zinc Plated	6mm-50mm
	304 Stainless Steel	13mm-50mm

# macsim<sup>®</sup>



### **DECKING SCREWS**

Type 17 Decking screws are for use in decking applications. They are suitable for use in ACQ Timber.

HEAD	PIN FINISH	LENGTH
Csk.	Galvanised	30mm-75mm
Self	304 Stainless Steel	30mm-125mm
Embed.	304 Stainless Steel	50mm-150mm
	316 Stainless Steel	50mm
	Green ACQ Coated	50mm-65mm
Csk. Self Embed.	304 Stainless Steel	50mm-65mm
Trim	316 Stainless Steel	40mm-65mm

### MACSIM® 🗐



## **SQUARE DRIVE DECKING SCREW T17**

- Imperial
- SS 304, SS 316





### **TORX DRIVE DECKING SCREW T17**

- Imperial
- SS 304, SS 316





## **NEEDLE POINT SCREW CSK**

- Imperial
- SS 304






STITCHING SCREWS

- Imperial - SS 316

Macsim Stitching Screws are a multipurpose screw used for general fixtures into timber or steel.



# MACSIM® 🗐



# TRADE PAX™ CONXTRUCT® ANCHORS



- Tygabolt® Anchors
- Xbolt® Anchors - Nail-in Anchors
- Suspension Anchors
- Pantha Plug®





### **TYPE 17 WASHER HEAD** T9PW3GI16





### SELF TAPPING CSK HEAD SQUARE DRIVE T04SSCQ



- Class 3
- 16 Gauge, Internal Hex
- 75, 100 & 125mm



- SS 304
- ANSI B18.6.4



### **TYPE 17 WASHER HEAD** T9PWTGO18



- Tykote Coating
- 18 Gauge, T40 Torx
- 75 250mm



### SELF TAPPING PAN HEAD SQUARE DRIVE T04SSPQ



- ANSI B18.6.4





### **TDX® TRIM HEAD 4 RIBS SQUARE DRIVE**

T04WSTD

- Decking Screw
- Type 17
- SS 304



### **SELF TAPPING SCREW PAN PHILLIPS**

- Imperial

- SS 304, SS 316





### **CSK HEAD 6 RIBS SQUARE DRIVE** T04WS6Q









### **SELF TAPPING SCREW CSK UNDERCUT PHILLIPS**



- SS 304





### **SELF TAPPING SCREW CSK SQUARE**

- Imperial
- SS 304





# **SELF TAPPING SCREW CSK PHILLIPS**

- Imperial

- SS 304, SS 316





## **SELF TAPPING SCREW PAN SQUARE**

- Imperial
- SS 304





### SERRATED FLAT HEAD **PHILLIPS**

T9PF3EP

- Framing Screw - Class 3





### **BUTTON HEAD SQUARE DRIVE** T16WSUQ





### FLAT HEAD PHILLIPS T9PNYLP

- Needle Point

- Zinc Yellow Passivated





### **SELF TAPPING SCREW CSK UNDERCUT SQUARE DRIVE**

- Imperial





### **HEX HEAD FLANGE** T9PF3FH

- Truss Framing Screw
- HEC
- Class 3





# **SCREWS AND AUTO-FEED SCREW SYSTEMS**

### **BUGLE BATTEN RIB HEAD HEX DRIVE**

T9PW3BH

- Type 17







### **HEXAGON HEAD COACH SCREWS**

- Metric
- SS 316





### **BUGLE BATTEN RIB HEAD HEX DRIVE** T9PWYBH

- Type 17

- Zinc Yellow Passivated



### **COACH SCREWS**

Coach Screws are mainly used for fixing into timber. The sharp point makes it easy to install, however pre -drilling is required in some instances.

HEAD	FINISH	DIAM.
Hex	Zinc Plated	6mm-12mm
	Galvanised	6mm-12mm
	316 Stainless Steel	6mm-12mm



### **BUGLE BATTEN 4 RIBS HEX DRIVE**

T04WSBH



### **BUGLE BATTEN SCREW T17**

- Imperial
- SS 304, SS 316





### TIMBER INSERT CSK HEX SOCKET HXTI16C



- HEC

- Left and right hand available

SERRATED FLAT HEAD



### **CHIPBOARD SCREWS**

Macsim Chipbaord screws have a coarse thread and fine shank to give a strong hold, grip & minimise stripout into soft timbers and chipboard. The countersunk self embedding head has 6 nibs to help remove chipboard pieces when countersinking.

HEAD	FINISH	DRIVE	LENGTH
Csk.	YZP & Gal	Phillips/ Square	19mm - 125mm
Self Embed.	304/316 Stainless	Phillips/ Square	25mm - 75mm
	EM	Square	25mm - 100mm



MACSIM® 3



# SUPER FLAT FRAMING **SCREW** T9PMKNP





- Black E-coat






### PILOT POINT PAN HEAD PHILLIPS T41PSPP

- SS 410

- ANSI B18.6.4





### **BATTEN SCREWS**

Type 17 Batten screws are a thread cutting screw for timber with a coarse tapping screw thread and special long sharp point which is fluted to catch timber chips. The shank of the batten screw is knurled to prevent timber splitting.

HEAD	FINISH	LENGTH
Csk. Self Embed.	Yellow Zinc Plated	50mm-100mm
	Galvanised	50mm-200mm
	304 Stainless Steel	50mm-150mm
	316 Stainless Steel	50mm-100mm
	EM Coated	50mm-200mm

# JMAX™ HEX HEAD FLANGE

T9PJ3FH

- Class 3 - Timber





### **ELECTRICAL PANEL SCREW PHILLIPS** T9PPZAP

- Zinc Plated

- HEC



