810 FIRE & ACOUSTIC

SupaFIRE

ADMIL

- Acrylic sealant
- AS1530.4 certified
- Acoustically rated
- Flexible ±15%
- Ideal for joints
  and penetrations
- Available in 600mL

FIRECRYL FR
131479 - 310mL
131478 - 600mL

SOUDAL

- Very good adhesion on most
  porous surfaces
- Fire resistant up to 4 hours
- Colourfast and waterproof after curing
- Stays elastic and can be
  painted over

PROSERIES FIREBLOCK

SELLEYS
IF IT'S SELLEYS IT WORKS!

A low modulus, non-slumping, PSA composite sealant
suitable for fire and acoustic rated construction*.

- Up to 4 hours fire rating in accordance
  with AS1530.4-2005 and ASTM E1966-07*
- Tested to ASTM E814-09 for penetrations
  in plasterboard lined walls
- Acoustic rated in 67Rw walls AS/NZIS0717-1
- UV indicator to confirm Fireblock usage
- Excellent adhesion to joint
  movement capabilities
- Paintable
- Isocyanate free
- Available in 600mL

*For fire rating, minimum joint width 40mm. Install backing
rod in joint to control sealant depth

SOUDASEAL FR
137450 - 290mL - Grey
131480 - 600mL - Grey
155483 - 600mL - Limestone

SOUDAL

- High level of fire retardation
- Outstanding bond strength on nearly
  all surfaces
- Permanently elastic after curing
- Colourfast and waterproof
  after curing
- Easy to use and apply

FIREBLOCK XT

SELLEYS
IF IT'S SELLEYS IT WORKS!

A fire and acoustic rated High Performance
SMP Sealant.

- Complies with BCA acoustic requirements
- Adhesion to damp surfaces
- No slump
- Paintable
- Low VOC
- Halogen and Isocyanate free
- Fire rated up to 4 hours according to AS1530.4
- Available in 600mL

FIRESOUND FIRE RATED ACOUSTIC SEALANT

H.B. Fuller

Firesound is formulated primarily to perform as a
barrier to the incursion of fire through expansion
joints and wall penetrations such as pipes or
cables. Firesound is also an effective acoustic
sealant.

Package	Format	Colour
450g Cartridge	15019213	Grey
600ml Sausage	15019215	Grey
600ml Sausage	15019147	White (MTO)
10L Pail	15019142	Grey

FULAFLEX FR HYBRID POLYMER FIRE RATED SEALANT

H.B. Fuller

FulaFlex FR is a high performance, elastomeric
and intumescent low-modulus fire resistant
construction sealant for use in interior and exterior
joint sealing applications and has been tested in
accordance with AS1530.4-2014. FulaFlex FR
combines excellent cold weather gun-ability with
bubble free curing in hot/humid climates.

Format	Product Code	Colour
600ml Sausage	15020051	Grey
600ml Sausage	15020158	Limestone

FIRETEK AC - Acrylic

MACSIM

Is a flexible, one component acrylic sealant, fire
rated up to 4 hours (AS/ 1530-PART 4, 2014) for
sealing interior & vertical exterior joints up to 40mm
wide, subject to movement accommodation. It is
water based, paintable and has low VOC.
(Replaces Fireseal 6)

SIZE	CODE	COLOUR
300ml	53FTAC300	Grey

FIREBAN ONE

Bostik Fireban® One is a fire rated intumescent, low modulus, one component, Class A polyurethane sealant. When cured it will form a tough, flexible fire rated seal capable of cyclic expansion and compression movement of 50% (±25%) of the original installed joint width.

- Fire Rated up to 4 hours
- Acoustic rated
- One component, no mixing required
- Low modulus 50 %(± 25%)
- Excellent durability

Product Codes
600ml sausage/20 per carton
Limestone - 30616836

FIREBAN ACRYLIC

Bostik Fireban® Acrylic is a single component, non-sag, fire rated acrylic based gunnable sealant.

- Fire rating for gaps up to 40mm
- Designed for Australian conditions
- Good flexibility joint movement +/- 25%
- One part no mixing required
- Very easy to apply and gives a smooth finish
- Low odour
- Non-toxic
- Asbestos free

Product codes
600ml Sausage/ 20 per Carton
Grey - 30615090
Limestone - 30615089

300ml Cartridge/20 per Carton
White - 30615088

FIREBAN EXPANDA FOAM

Bostik Fireban® Expanda Foam is a ready to use, self-expanding, polyurethane foam with fire resistant up to a period of 2 hours as per AS1530.4 -2014.

- Fire resistant up to 120 minutes
- Meets AS 1530.4 – 2014
- Efficient seal against smoke and gas
- Excellent thermal and acoustic insulation
- High bonding strength
- Very good filling characteristics

Product codes
600ml Sausage/ 20 per Carton
Grey - 30615090
Limestone - 30615089

300ml Cartridge/20 per Carton
White - 30615088

SOUDAFOAM SMX
113839 - 500mL
- 100% isocyanate free foam
- Filling of cavities
- Improving thermal isolation
- Very good bonding properties
- High filling capacity
- Sealing horizontal and vertical joints in wall and roof connections

SOUDAFOAM FR
108289 - 750mL - Straw
123233 - 750mL Gun - Screw Top

- Fire retardant up to 360 min
- Efficient seal against smoke and gas
- Excellent adhesion on most substrates
- High thermal and acoustical insulation
- Non shrink
- Meets Aust Standard AS1530.4-2005

FULAFOAM
TRIPLE EXPANDING FOAM FILLER

FulaFoam Expanding Foam is a triple expanding, general purpose, polyurethane foam that will fill cavities ranging in size from small gaps to larger spaces. FulaFoam Expanding Foam will adhere to a wide range of substances and will provide an airtight, moisture resistant seal when cured.

Format	Product Code	Colour
300ml Can	15019422	Yellow
500ml Can	15019421	Yellow
750ml Can	15019420	Yellow
Fire Resist.750ml Can	15019396	Pink

FULAFOAM PRO GUN
FOAM FILLER

FulaFoam Pro Gun applied foam is available in two versions: triple expanding, and low expansion (flexible). Both are general purpose, polyurethane foams that will seal against noise and moisture, as well as fill holes and penetrations. Suitable for use with many commonly used building materials, including polystyrene.

For clean up use FulaFoam Gun & Foam Cleaner, a solvent based cleaner for removing uncured foam from applicator guns, tools and other surfaces.

Format	Product Code	Colour
Triple Exp 750ml Can	15019467	Yellow
Low Exp 750ml Can	15019976	Green
Cleaner 500ml Can	15020102	-