BT 600 Z KNOTTED WIRE CUP BRUSH

- For aggressive brush work on large, flat surfaces
- For preparing metal surfaces before varnishing
- Stable knotted wire design for easy cleaning and removal of slag, rust, scale and concrete residue



Product Code	Size (mm)	Specification	Max RPM
358335	65 x M14	Steel	12,500
358340	65 x M14	S/Steel	12,500

BR 600 Z KNOTTED WIRE WHEEL BRUSH

- Wheel brush for pre- and postprocessing of welding seams
- For aggressive removal of scale, rust and slag
- For heavy brushing and deburring work



Product Code	Size (mm)	Specification	Max RPM
358312	125 x 14 x 22.23	Steel	12,500
358343	125 x 14 x 22.23	S/Steel	12,500

BK 600 Z KNOTTED WIRE CONE BRUSH

- Ideal tool for working on hard to reach areas, inside corners and bevels
- High brushing capacity due to knotted wire design
- Excellent for cleaning larger surfaces
- Removal of scale, rust, paint, slag, etc.



		Lateral adoptions		
Product Code	Size (mm)	Specification	Max RPM	
358328	115 x M14	Steel	12,500	
358330	115 x M14	S/Steel	12,500	

CUP BRUSHES TWIST KNOT STEEL

- Excellent for heavy duty brushing
- Special quality wire with high flexibility & fatigue resistance
- Suitable for work on large surfaces, deburring, cleaning and rust removal



R PFERD

Article No.	Size mm	Thread	Max. RPM	
47701009	65	M14 / M10	12,500	1
47701479	65	M10 x 1.5	12,500	1

BR 600 W CRIMPED WIRE WHEEL BRUSH

- Suitable for low to medium duty brushing and deburring of cut edges, tubes or small parts
- For use on stationary machines
- Included adaptor set for shaft diameters 12.7mm, 16mm, 19mm, 22.2mm and 25.4mm



Product Code	Size (mm)	Specification	Max RPM
363997	150 x 25 x 32	Steel	6,000
364000	150 x 25 x 32	S/Steel	6,000
363999	200 x 25 x 32	Steel	4,500
364002	200 x 25 x 32	S/Steel	4,500

FLARED CUP BRUSHES TWIST KNOT COMBITWIST STEEL

- Excellent for heavy duty brushing in hard to reach areas
- The patented COMBITWIST construction enables smooth operation, even on corners & edges
- Enhanced brush life and increased stock removal





Article No.	Size mm	Thread	Max. RPM	
43313011	100 x 13	M14	20,000	1
43317011	125 x 15	M14	15,000	1

BRP 600 Z KNOTTED WIRE PIPELINE BRUSH

- Ideal tool for the professional processing of UV type welds in pipline, pipework and container construction
- Due to its slim overall width it is also well suited for working on hard to reach areas



Product Code	Size (mm)	Specification	Max RPM
358315	125 x 6 x 22.23	Steel	12,500
363992	125 x 6 x 22.23	S/Steel	12,500

BENCH WIRE WHEELS STEEL

- Suitable for medium heavy duty brushing such as scale removal, rust removal, light deburring & cleaning of weld seams
- Extremely high filament density for aggressive brushing & long brush life
- Bushes included



翠PFERD

Article No.	Size in/mm	Max. RPM	B
43740015	(6") 150 x 20	6,000	1
43740017	(8") 200 x 20	4,500	1

CUP BRUSHES WITH CRIMP OR TWIST KNOT WIRE. AVAILABLE WITH STEEL OR 316 STAINLESS STEEL WIRE.

- Diameters from 50mm to 125mm.

















BEVEL BRUSHES WITH CRIMP OR TWIST KNOT WIRE. AVAILABLE WITH STEEL OR 316 STAINLESS STEEL WIRE.

- Diameters from 75mm to 125mm.













WIRE WHEELS WITH CRIMP OR TWIST KNOT WIRE. AVAILABLE WITH STEEL OR 316 STAINLESS STEEL WIRE.

- Diameters from 85mm to 300mm.



TWIST KNOT STEEL WIRE PIPELINE BRUSHES.

- Diameters from 125mm to 178mm.











the name behind the names,

CSS Members: Australian Owned & Independently Operated. **100 plus** stores nationwide.