FULL BLOW CUPLA SOCKETS





CUPLA





- · No residual pressure on connection or disconnection
- Safety Lock Mechanism Safety Purge Function
 - · Full unrestricted air flow

Model No.	Application	Model No.	Application	
For Female Connection		For Male Thread Connection (SF)		
FBH-20SM	1/4"	FBH-20SF	1/4"	
FBH-30SM	3/8"	FBH-30SF	3/8"	
FBH-40SM	1/2"	FBH-40SF	1/2"	







- · Safety Lock
- · Purge Mechanism
- · Suitable for Mining and Construction use

Model No.	Application	Model No.	Application	Model No.	Application
For F Connect		For Fema Connect		For Male Connect	
PVR-400SH	1/2"	PVR-400SN	1 1/2"	PVR-400SF	1/2"
PVR-600SH	3/4"	PVR-600SM	1 3/4"	PVR-600SF	3/4"
PVR-800SH	l 1"	PVR-800SM	1 1"	PVR-800SF	1"

200 SERIES LOCK CUPLA **SOCKETS**



PURGE PLUGS & ROTARY PLUGS





Connection (SH)

L-20SH

L-30SH

L-40SH



Model No. Application | Model No. Application | Model No. Application For Female Thread

Connection (SM)

1/4'

3/8"

1/2"

L-20SM

L-30SM

L-40SM



	10.0
Purge	





Model No.	Application	Model No.	Application	Model No.	Application	
For Hose Connection (PH)			ale Thread tion (PM)	For Parallel Male Thread Connection (PFF)		
PV-20PH	1/4"	RL-20PM	1/4"	RL-20PFF	1/4"	
PV-30PH	3/8"	RL-30PM	3/8"			
PV-40PH	1/2"					

POLYURETHANE COILED HOSES

1/4"

3/8"

1/2



For Male Thread

Connection (SF)

1/4"

3/8"

1/2'

CUPLAS MADE

L-20SF

L-30SF

L-40SF









Hose Part No.	Size	Working Length
HA0803B / HA0805B/ HA0808B / HA0810B	8 x 5mm	2m / 4m / 6m / 8m
HA1003B / HA1005B/ HA1008B / HA1010B	10 x 6.5mm	2m / 4m / 6m / 8m
HA1203B / HA1205B/ HA1208B / HA1210B	12 x 8mm	2m / 4m / 6m / 8m

CRIMPED HOSE ASSEMBLIES





IN USA

Crimped Hose Complete with **Митто конк**і 200 Series Hi-Cupla

Hose Length	Hose Size
10 metres	9.5mm (3/8")
20 metres	9.5mm (3/8")
30 metres	9.5mm (3/8")
10 metres	12.7mm (1/2")
20 metres	12.7mm (1/2")
30 metres	12.7mm (1/2")
	10 metres 20 metres 30 metres 10 metres 20 metres

S SERIES HOSE REELS

- Quality impact resistant UV stabilised covers for maximum durability
- Detachable steel mounting bracket enables 180° hose reel rotation
- Automatic & positive latching mechanism
- Adjustable hose stop for convenient lead length positioning



Product No.	Product Description	Hose Length	Hose ID	Working Pressure	Hose Material	Cover Colour	Hose Colour	Max. Working Temp.	Reel Inlet BSPT(m)	Hose Outlet BSPT(m)	Weight
SA300N	Air Hose Reel	18m	10mm	300psi (20bar)	Hybrid Polymer	Red	YELLOW	-10°C~60°C	3/8"	3/8"	10kg
SA400N	Air Hose Reel	15m	12mm	300psi (20bar)	Hybrid Polymer	Red	YELLOW	-10°C~60°C	1/2"	1/2"	10kg
SAW100	Air & Water Hose Reel	16m	10mm	300psi (20bar)	PVC	Red	BLUE	0°C~60°C	3/8"	3/8"	10kg
SAW200	Air & Water Hose Reel	13m	12mm	300psi (20bar)	PVC	Red	BLUE	0°C~60°C	3/4"	3/4"	10kg

ALEMLUBE EL SERIES AIR HOSE REEL HR40030

- Supplied complete with 20m x 10mm ID PVC hose & 0.9m lead in hose
- High quality impact & UV resistant polypropylene covers
- 3/8" BSP(f) inlet/outlet
- Maximum working pressure of 300psi (20bar)
- HR40040 Also available with 15m x 12mm ID PVC hose




Alemlube

ogeiger.

SAMOA 3/4" SPRING REWIND FUEL, **OIL, AIR & WATER HOSE REEL** 505224N

- Heavy duty full metal double pedestal construction
- Hose capacity 15m x 19mm ID
- Hose pressure rating 1,500psi (103bar)
- 3/4" BSP(f) inlet/outlet
- Seven position outlet arm



- 20m x 12mm ID



Alemlube



ALEMLUBE EL SERIES AIR, WATER & FUEL SPRING REWIND HOSE REEL HR90040

- Reinforced steel frame provides maximum strength & stability
- Includes 30m x 12mm ID rubber hose & hose stop
- HR90040 30m x 1/2" ID hose 25m x 1/2" ID hose - HR90045 20m x 3/4" ID hose - HR90025
- HR90005 30m x 1" ID hose 8m x 1" ID hose - HR90015



20M MANUAL HOSE REEL GPHR1220



Hose Size: 20 Metre x 11 mm ID

- High quality Polyurethane braided hose
- Space Saving Foldable Handle
- 360 degree
- swivel base

20M WALL MOUNT HOSE REEL **GPHR1020**

Hose Size: 20 Metre x 11 mm ID

- 180° swivel bracket
- 1.5 metre inlet hose
- High quality braided
- polyurethane hose
- Sheet metal housing
- Adjustable recoil stopper
- Shrouded air line socket



RECOIL AIR HOSES





geiger.

- One-Touch couplings
- Made from kink resistant polyurethane

Product Code	Length	Hose Size
GPH1003LBHL	2 Metre	6.5 MM ID x 10 MM OD
GPH1006LBHL	5 Metre	6.5 MM ID x 10 MM OD
GPH1008LBHL	6 Metre	6.5 MM ID x 10 MM OD
GPH1010LBHL	8 Metre	6.5 MM ID x 10 MM OD
GPH1206LBHL	5 Metre	8 MM ID x 12 MM OD
GPH1208LBHL	6 Metre	8 MM ID x 12 MM OD
GPH1210LBHL	8 Metre	8 MM ID x 12 MM OD
GPH1212LBHL	10 Metre	8 MM ID x 12 MM OD