# **BUILDERS HARDWARE**

#### **ULTRALOC - THREADLOCKERS** 50ML 3222

The most reliable method to lock and seal threaded fasteners. From easy removal small threads under 6mm to permanent high strength over 25mm. Available in varying viscosities and strengths for virtually any application. Prevents loosening of fasteners, seals against corrosion, provides correct lubricity, controlled strengths, suitable for all fastener sizes, easy to apply.



#### **ULTRALOC - RETAINING** 300ML 3609

Anaerobic retaining compounds fill the 'inner space' between components and cure to form a strong precision assembly. Formulated in a wide range of viscosities, gap fill flexibility and strength characteristics.

- · Increased assembly and product reliability
- · Fills all voids and ensures 100% contact
- · Seals against corrosion · Controlled



ULTRA LOC

# **PVC PIPE CEMENT - TYPE P**

222518 - 125mL

222514 - 250mL / 222488 - 250mL (Clear) 222515 - 500mL / 222516 - 500mL (Clear)

- High bond strength in all pressure applications
- No mixing required and ready to use
- Watermark certified and independently tested



# **PVC PIPE CEMENT - TYPE N**

222507 - 125mL

222508 - 250mL / 222487 - 250mL (Clear) 222509 - 500mL / 222512 - 500mL (Clear)

222510 - 1L

222511 - 4L / 222513 - 4L (Clear)


- Bonding PVC pipe and fittings with a diameter of 10cm or less
- No mixing required and ready to use
- Approved for contact with drinking water
- Complies with AS/NZS 4020





## **TRADIE'S BOG**

- A building filler that is easy to sand and provides fast repairs to timber and most common building materials.
- Easy to sand
- Excellent adhesion
- Sets hard in 20 minutes
- Can be sawn, drilled, tapped, sanded and painted
- Can be coloured with cement oxides or paint tinters





### **LIGHT SPEED FILLER**

132673 - 250mL 132672 - 900mL



- Rapid drying
- Light weight
- Smooth finish
- Very good adhesion on many porous materials





SOUDAL

SOUDAL

SELLEYS



# **UNIVERSAL BOG**

132560 - 750gr 132561 - 1.5kg

- Smooth and easy to apply
- Repairs gaps, cracks, holes and dents
- Will not rot and remains waterproof
- None shrink, slump / sag
- Sandable



### POINT WORKS POINTING COMPOUND

Point Works forms an incredibly strong and durable bond between the tiles and the ridge, and the smooth non-slumping consistency makes it easy to mix and apply. It is the first pointing compound to qualify as an Adhesive Mechanical Fastener for hip and ridge tiles in accordance with AS2050-2018. Point Works has also passed the fatigue loading for both Cyclonic Conditions C3 and C4 after conditioning by prolonged water saturation as per Australian Standard AS AS4046.8-2015.

- Best for new roofs and repairs
- Flexes with normal roof movement
- Sag resistant
- Water clean up
- Available in 13 colours: Black, Grey, Mahogany, Crimson, Grey, Dark Grey, Charcoal, Terracoitts, Walnut, Neutral, Burnt Orange, Desert Red and Outback Red
- Range also includes 5L Accelerant





