





## WE ARE WATERPROOFING



### Sika® Tite® BE



Sika® Tite BE is a heavy duty, highly flexible, waterbased bitumen waterproofing membrane. Suitable for use below ground as a damp proof sandwich membrane, foundation and basement walls, retaining walls and planter boxes.

**COLOURS**  
• Black

**PACKAGING**  
• 4 L PAIL  
• 15 L PAIL



### Sikalastic®-1K



Sikalastic®-1K is a one-component, crack-bridging, fibre-reinforced mortar, based on cement modified with special alkali-resistant polymers. Sikalastic®-1K is suitable for application by brush, spray or trowel.

**COLOURS**  
• Light Grey

**PACKAGING**  
• 20 kg BAG  
• 10 kg PAIL



### Sikalastic® Moisture Seal



Sikalastic® Moisture Seal is a two part, water-based, epoxy which chemically cures to form a waterproof vapour barrier that is hydrostatic pressure resistant and can prevent rising damp.

**PACKAGING**  
• 20L Kits  
(10 L Part A + 10 L Part B)



### SikaSwell® S-2



SikaSwell® S-2 is a 1-part polyurethane hydrophilic sealant which swells in contact with water to seal all types of construction joints and penetrations in concrete.

**COLOURS**  
• Oxide red

**PACKAGING**  
• 300 ml CTG  
• 600 ml SSG

## FOSROC NITOPROOF 210

Nitoproof 210 is a high performance single component water based bituminous rubberised liquid applied waterproofing membrane, which contains root inhibiting additives.



## FOSROC NITOPROOF 310

Nitoproof 310 is a fibre enhanced single component water based latex liquid applied membrane, designed for waterproofing applications where the membrane is to be covered over with tiles, screeds or concrete beds. Nitoprime 120 required on concrete or porous surfaces before applying Nitoproof 310.



Product Code	Description	Size
FC000605-15L	Nitoproof 210 15L	15L

Product Code	Description	Size
FC000602-15L	Nitoproof 310 15L	15L

## FOSROC NITOPROOF 410

Nitoproof 410 is a water based, fast drying, flexible two component, polymer modified, cementitious waterproofing membrane designed for under toppings, tiles and other protected environments. It may also be used for foot trafficable exposed roof top membranes and foot trafficable exposed balcony decks when overcoated with Nitoproof Top Coat UV. Nitoprime 120 required on concrete or porous surfaces before applying Nitoproof 410.



## LEAKMASTER

Leakmaster is a gun applied, water-swellable, waterstop paste manufactured by C.I. Takiron Corp. for bonding Hydrotite profiles to rough concrete surfaces. It can also be used as a stand-alone water sealing non-movement joints of cast-in-situ concrete.



Product Code	Description	Size
FC000603-12.5L	Nitoproof 410 Part A 12.5L	20L PACK
FC000604-12.5KG	Nitoproof 410 Part B 12.5KG	

Product Code	Description	Size
FC000785-UNIT	Leakmaster 320ml	320ml

## FOSROC SUPERCAST PVC WATERSTOPS

Supercast PVC waterstops are designed to provide an integral sealing system for movement and construction joints in cast or concrete. The range consists of centrally placed profiles; Supercast Hydrofoil and Rearguard externally placed profiles. Supercast PVC waterstops are available as straight lengths (rolls) and factory produced intersections.



## HYDROTITE

Hydrotite is a hydrophilic waterstop manufactured by C.I. Takiron Corp. which expands in a controlled manner in the presence of moisture to create a pressure seal within construction joints in concrete structures.



Product Code	Description	Size
FC020303-UNIT	Supercast PVC Waterstops Hydrofoil 250mm x 12m	250mm x 12m Roll

Product Code	Description	Size
FC000560-UNIT	Hydrotite DSS0220 ADH / 25m roll	2mm x 25mm roll
FC000550-UNIT	Hydrotite CJ0725-3K ADH / 10m roll	7mm x 10mm roll
FC000555-UNIT	Hydrotite CJ1020-2K ADH / 10m roll	10mm x 10mm roll
FC000580-UNIT	Hydrotite RSS1610D / 10m roll	16mm Diameter
FC000455-UNIT	Hydrotite RSS2014D / 10m roll	20mm Diameter
FC000595-UNIT	Hydrotite RSS2205D / 10m roll	22mm Diameter
FC000545-UNIT	Hydrotite RSS2519D / 5m roll	25mm Diameter

## DAMPFIX PLATINUM 30614346

- Class 3, high elasticity
- Fast drying. Recoat in 1-2 hours @ 22°C & 50% RH. Flood test after 24 hours @ 22°C / 50% RH.
- Can be tiled after 4-6 hours @ 22°C / 50% RH in non-critical areas.
- Compatible for tiling with Bostik tile adhesive systems.
- 15 Litre pail



## DAMPFIX 1K 30615232

- One component, flexible, fibre-reinforced
- Suitable for both negative and positive hydrostatic pressure to 5 bars (50 Meters)
- Fast drying. Recoat in 1-2 hours
- Class 1, low extensibility when tested to Australian standard AS 4654 .1 & AS/ NZS4858
- AS4020:2018 - potable water certificate
- 20kg bag



## DAMPFIX GOLD 30800489

- Class 3, high elasticity
- Fast drying
- Recoat in 2 hours @ 20°C & 50% RH
- Early access for following trades
- Tile next day in most conditions
- May be tiled directly using approved Bostik tile adhesives
- Reinforced with clump free fibers
- 15L Pail



## DAMPFIX INSTANT SEAL TAPE

Dampfix® Instant Seal waterproofing tape seals joints, corners, and drainage pipe outlets, and is used as a bond breaker in the Dampfix® waterproofing membrane system.

**Product codes**  
Contact your Bostik representative



## SOUDAGUM HYDRO 134553 - 1kg Repair kit 131634 - 5kg 131632 - 10kg

- Hybrid waterproof liquid membrane
- Ready to use, one component
- Excellent workability, can be applied in 2 layers
- Rain resistant 2hrs after application
- Solvent / Isocyanate free

