

DAMPFIX PLATINUM 30614346

- Class 3, high elasticity
- Fast drying. Recoat in 1-2 hours @ 22°C & 50% RH. Flood test after 24 hours @ 22°C / 50% RH.
- Can be tiled after 4-6 hours @ 22°C / 50% RH in non-critical areas.
- Compatible for tiling with Bostik tile adhesive systems.
- 15 Litre pail



DAMPFIX 1K 30615232

- One component, flexible, fibre-reinforced
- Suitable for both negative and positive hydrostatic pressure to 5 bars (50 Meters)
- Fast drying. Recoat in 1-2 hours
- Class 1, low extensibility when tested to Australian standard AS 4654 .1 & AS/ NZS4858
- AS4020:2018 - potable water certificate
- 20kg bag



DAMPFIX GOLD 30800489

- Class 3, high elasticity
- Fast drying
- Recoat in 2 hours @ 20°C & 50% RH
- Early access for following trades
- Tile next day in most conditions
- May be tiled directly using approved Bostik tile adhesives
- Reinforced with clump free fibers
- 15L Pail



DAMPFIX INSTANT SEAL TAPE

Dampfix® Instant Seal waterproofing tape seals joints, corners, and drainage pipe outlets, and is used as a bond breaker in the Dampfix® waterproofing membrane system.

Product codes
Contact your Bostik representative



SOUDAGUM HYDRO 134553 - 1kg Repair kit 131634 - 5kg 131632 - 10kg

- Hybrid waterproof liquid membrane
- Ready to use, one component
- Excellent workability, can be applied in 2 layers
- Rain resistant 2hrs after application
- Solvent / Isocyanate free

