



# Impact-A Roof & Gutter

## Description

Impact-A Roof & Gutter Premium (100%) silicone is a one component, mid modulus, neutral curing silicone which provides excellent adhesion to many common substrates.

## Classifications/Standards

Translucent and Grey are suitable for drinking water Applications (AS/NZS4020-2005) Bostik Australia retested 2010 and approved by AWQC.

## Features

- Excellent adhesion properties
- Stays permanently flexible
- Joint Movement capabilities  $\pm 25\%$
- Suitable for interior and exterior applications
- Unaffected by rain, snow, extreme temperature change
- Ultra violet resistant
- Suitable for water potable applications \*
- Translucent & Grey tested to AS/NZS 4020 \*
- Weather Proofing
- Excellent shelf life

## Recommended Uses

- Plumbing Roofing applications
- Metal roofing systems
- Metal water tanks
- Spouting/flashing and downpipes
- Lap joints in Zinalume, Colorbond and other decorative sheet metal
- Skylights and metal and PVC flues and extraction units
- Pipe or sprinkler system penetrations
- Air conditioning ducting and sheet-metal fabrications
- General purpose adhesive and sealant for building materials such as steel, aluminium, glass, concrete, brick, Ceramic, Terracotta roof tiles.

## Application Instructions

### Surface Preparation

Surfaces to be sealed must be clean, dry and free of wax, grease, cutting oils or any loose or flaking materials. Use the two-wipe process for impervious substrates. Ensure the cloths are clean and changed frequently, and use a suitable cleaner/solvent such as 100% White Spirits.

To achieve satisfactory adhesion a primer may be required for some substrates.

### Application

Use masking tape each side of joint to simplify clean up, to protect surfaces and to ensure a neat job.

Use a closed cell polyethylene-backing rod 25% larger than the joint width, to control the depth of the joint where required.

Cut nozzle at 45° angle to desired thickness. Cut opening on cartridge and fix nozzle. Insert cartridge into



# Impact-A Roof & Gutter

caulking gun. Hold gun at 45° angle with nozzle in contact with both sides of joint. Apply by pushing sealant ahead of nozzle, thus ensuring sealant is pushed firmly into place.

Tool off / smooth before skin forms (within 5 minutes). Remove excess sealant immediately with a cloth dampened with mineral turpentine or Zbond® R-40. If used, remove masking tape before skinning has started.

(Cured sealant can be removed by trimming with a sharp blade).

The incompatibility of some substrates may cause discolouration of sealant, poor sealant adhesion or long term degradation of the sealant. Always carry out compatibility tests where contact with potentially incompatible materials occurs.

### Coverage

Approximately 16 lineal metres per 300ml cartridge based on an average joint size of 6 mm depth and 3 mm width

### Setting Time

Sealant will skin over within 5 minutes (subject to humidity in air – lower the humidity longer time to skin over and cure, high humidity shorter skin and cure time).

### Limitations

Impact-A Roof & Gutter is ***NOT*** suitable for use in the following applications: -

- Totally confined spaces as the sealant requires atmospheric humidity to cure, it will not cure where it does not have access to atmospheric humidity.
- Aquariums
- Adhering Mirrors (Bostik V60 can be used - test first)
- Structural Glazing (Bostik V70 – refer to Bostik guide lines first).
- Composite panels- (Bostik recommends Bostik 5CLM- subject to test first)
- Under Water Applications (including swimming pools subject to substrate). Refer to Bostik for these applications.
- Below Grade Applications
- All Stone (We recommend the completion of a stain testing program before using any sealant on stone) Bostik 5CLM is recommended for marble, granite (after stain test).
- Horizontal walkways and trafficable areas
- Polycarbonate sheeting
- Sealant may discolour copper & brass.
- Do not clean or treat the sealant with materials, cleaning agents or solvents that may affect or discolour the sealant, particularly during product curing.
- **This silicone is not paintable.**

### NOTE:

Silicones are not always compatible with plasticised sealants, such as butyls. Also note that some backing rods and tapes contain bitumen or other agents that are incompatible with the silicone.

If there is a requirement to paint the sealant, use Bostik Paintable silicone sealant or Bostik Fill-A-Gap acrylic sealant products. Refer to Technical Data Sheet of product for appropriate application and follow both the sealant and paint manufacturers painting instructions carefully, when painting these sealants.

### TIP

*For granite, marble or porous masonry and stone materials, Bostik Plumb Seal (non Silicone) can be used. Always test product in a small inconspicuous area before using. Plumb Seal is also paintable.*

**IT IS IMPORTANT TO NOTE:** Oxime silicone sealant will tend to display a slight colour shift with age.

Chemical exposure to certain agents such as chlorinated cleaning solutions (ie, bleach), chemical solvents, and the fumes of some paints (enamel or solvent – containing types where not fully dried) may tend to magnify this yellowing change particularly where the sealant is still curing.



# Impact-A Roof & Gutter

## Properties

Colour	Various colours	Hardness Shore A (ASTM D-2440)	20
Tooling / Skin Time @ 20°C	5 Minutes approx.	Tensile Strength (ASTM D-412)	1.5 MPa
Tack Free Time @ 20°C (ASTM C-679)	30 minutes approx.	Sag, Slump	0
Cure Time (To 10mm depth @ 23°C & 50% RH)	5-7 days	Specific Gravity	1.03
Application Range	+10°C to + 40°C	Cure Method	Neutral - Oxime
Performance Range	- 50°C to +170°C		

## Storage & Shelf Life

Store between 5°C-25°C in a dry, ventilated area, out of direct sunlight.

The shelf life of Impact-A Roof & Gutter is 18 months from date of manufacture when stored in recommended conditions.

## Health & Safety

### CAUTION

Full product safety information required for safe use is not included in this data sheet. Before handling, read the separate Material Safety Data Sheet (MSDS) and packaging for safe use. Always read the Technical Data Sheet and Material Safety Data Sheet (MSDS) before opening or using this product.

In case of product emergency refer to product labelling or MSDS and contact phone numbers. A copy of the product MSDS is available from [www.constructionsupply.com.au](http://www.constructionsupply.com.au)

### FIRST AID

If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766)

**SEE THE MATERIAL SAFETY DATA SHEET FOR ADDITIONAL INFORMATION. EMERGENCY INFORMATION: 1800 033 111 (ALL HOURS)**

## Packaging

300ml cartridges and 600ml foil sausages

## Product Details

Item Number	Size	Colour	Pack Quantity
241008	300g cartridge	Translucent	20
241016	300g cartridge	Grey	20

